	1		2		3	4	5	
			6.0			COMPLIANCE: LEA ELECTRICAL INSULATOR RESIS	N 66 FING: UL94-V0 ERATURE: -25°C UP TO 85°C D FREE AND ROHS TANCE: >1000 MOHM STANDING VOLTAGE: 800V AC/MN	
		4.5 A-A'		2.00 TYP.		DIMENSION A = 2.00 x (NB. PIN B = 2.00 x (NB. PIN C = 2.00 x (NB. PIN	+ 0.60	
G F E D	oHS Compliant 20-NOV-15 26-MAY-14 06-AUG-13 17-NOV-09	C DIMENTION OPE TEMPERATURE CHARACTERISTIC STANDARD	ES QL QL JP	A±0.25 C±0.5	GENERAL TOLERANCE .X = +/_ 0.2 .XX = +/_ 0.15	WÜRTH ELEKTRONIK		
G F E D C	20-NOV-15 26-MAY-14 06-AUG-13 17-NOV-09 28-OCT-09	OPE TEMPERATURE CHARACTERISTIC STANDARD W. VOLTAGE	QL QL JP JP	C±0.5	.X = +/_ 0.2 .XX = +/_ 0.15 UNIT: MM	WÜRTH ELEKTRONIK DESCRIPTION: 2.00 MM FEMALE TERMIN	AL HOUSING SIZ	Έ
G F E D	20-NOV-15 26-MAY-14 06-AUG-13 17-NOV-09	OPE TEMPERATURE CHARACTERISTIC STANDARD	QL QL JP		.X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15			2E 4

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE]
F					.X = ⁺ / ₋ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONIK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	חך
В]	SCALE:			Γ
A	10-SEP-14	PDF	QL]	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY]	DRAW: QL			