



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

2SB1140-R 2SB1140-S

Features

- Power dissipation: $P_{CM} = 0.5W(T_{amb}=25^{\circ}C)$
- Collector current: $I_{CM} = -2A$
- Collector-base voltage: $V_{(BR)CBO} = -50V$
- Operating and storage junction temperature range
 $T_J, T_{stg}: -55^{\circ}C$ to $+150^{\circ}C$
- Case Material: Molded Plastic. UL Flammability
 Classification Rating 94V-0 and MSL Rating 1
- Halogen free available upon request by adding suffix "-HF"

Electrical Characteristics @ 25°C Unless Otherwise Specified


Symbol	Parameter	Min	Typ	Max	Unit
V_{CEO}	Collector-Emitter Breakdown Voltage ($I_C=-1000 \mu A, I_B=0$)	-50	---	---	V
V_{CBO}	Collector-Base Breakdown Voltage ($I_C=-10 \mu A, I_E=0$)	-50	---	---	V
V_{EBO}	Emitter-Base Voltage ($I_E=-10 \mu A, I_C=0$)	-5.0	---	---	V
I_{CBO}	Collector Cut-off Current ($V_{CB}=-50V, I_E=0$)	---	---	-1.0	μA
I_{EBO}	Emitter Cut-off Current ($V_{EB}=-5V, I_C=0$)	---	---	-1.0	μA
h_{FE1}	DC Current Gain ($V_{CE}=2V, I_C=0.2A$)	120	---	340	---
h_{FE2}	DC Current Gain ($V_{CE}=2V, I_C=1A$)	60	---	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=1A, I_B=50mA$)	---	---	-0.3	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=1A, I_B=50mA$)	---	---	-1.2	V
f_T	Transition Frequency ($V_{CE}=10Vdc, I_C=50mAdc, f=200MHz$)	---	80	---	MHz
C_{ob}	Collector output capacitance ($V_{CB}=-10V, I_E=0, f=1MHz$)	---	---	80	PF

CLASSIFICATION OF h_{FE}

Rank	R	S
Range	120-240	170-340
Marking	1L	

PNP Plastic-Encapsulate Transistors

SOT-89



DIM	DIMENSINS				NOTES
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.173	.181	4.39	4.60	
B	.063	.071	1.60	1.80	
C	.154	.165	3.91	4.25	
D	.031	.039	0.80	1.00	
E	.092	.100	2.34	2.54	
F	.118	----	3.00	----	TYP
G	.013	.019	0.33	0.48	
H	.015	.021	0.38	0.53	
J	.015	.016	0.38	0.41	
K	.055	.063	1.40	1.60	



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape & Reel; 1 Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.