			PART NO. FOR #4 (M3 SCREW		(M3.5) F	PART NO. OR #8 (M4) SCREW	PART NO. FOR #8 (M4) SCREW	DIM. "A" ±.015 [0.4]
			SRS4-2-01					1/8 [3.2]
			SRS4-3-01		;	SRS8-3-01	SRS8-2-3-01	3/16 [4.8]
			SRS4-4-01	SRS6	-4-01	SRS8-4-01	SRS8-2-4-01	1/4 [6.4]
			SRS4-5-01	SRS6	-5-01	SRS8-5-01	SRS8-2-5-01	5/16 [7.9]
			SRS4-6-01	SRS6	-6-01	SRS8-6-01	SRS8-2-6-01	3/8 [9.5]
A			SRS4-7-01	SRS6	-7-01	SRS8-7-01	SRS8-2-7-01	7/16 [11.1]
			SRS4-8-01	SRS6	-8-01	SRS8-8-01	SRS8-2-8-01	1/2 [12.7]
			SRS4-10-0	1 SRS6-	·10-01 S	SRS8-10-01	SRS8-2-10-01	5/8 [15.9]
			SRS4-12-0	1 SRS6-	12-01 5	SRS8-12-01	SRS8-2-12-01	3/4 [19.1]
			SRS4-14-0	1 SRS6-	14-01 5	SRS8-14-01	SRS8-2-14-01	7/8 [22.2]
' Ι Ψ Ι Ι	$\square \square \square$		SRS4-16-0	1 SRS6-	·16-01 S	SRS8-16-01	SRS8-2-16-01	1 [25.4]
			L		I			
			SERIES NO.	"B"	"C"	"D"	MOUNTING HOLE DIA. ±.003 [0.08]	MOUNTING PANEL THICKNESS
		-	SRS4	1/4 [6.4]	.125 [3.2]	1	.187 [4.7]	
		-	SRS6	9/32 [7.1]	.153 [3.9]	1/8 [3.2]		.062 [1.57]
"D" "D"	→ "C" →		SRS8			-	.234 [5.9]	
	SECTION A-A	-	SRS8-2	9/32 [7.1]	.169 [4.3]	.152 [3.85]		.087 [2.2]
NOTES:	SCALE 3 : 1	L						
 STANDARD MATERIALS: -NYLON 6/6 UL 94 V-2 (RMS-01), COLOR NATURAL. -FLAME RETARDANT NYLON 6/6 UL 94 V-0 (RMS-19), COLOR NATURAL. ALTERNATE MATERIAL AVAILABLE BY SPECIAL ORDER ONLY: -HEAT RESISTANT NYLON (RMS-109), COLOR NATURAL. TO ORDER, REPLACE "-01" WITH "-109" ALTERNATE UNITS FOR REFERENCE ONLY 								
H ADDED SRS8-3-01 PART, SEE CO 200679 SK 06/08/2011	CREATED USING SOLIDWORKS TOLERANCES	FILE #: SRS SHEET: 1 OF 1 SH		DWN: SK DT: 09/28/05		P: RT KD: SJ	FIN PART #	
G ADDED SRS8-2 SERIES, SEE CO 200676 SK 06/06/2011	UNLESS NOTED							PRINT TYPE
- SEE ENGINEERING FOR REV. A - E	.XXX=±.005 FRAC.=±1/64	RICHCO, I	NC.	ENG	RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		SEE TABLE CA	
REV. DESCRIPTION ENGR. DATE	ANG.=±1°			(7	(73) 539-40	60		