

## Device connector, front mounting - RC-16P1N8A2300 - 1614959

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Device connector for front wall, straight, shielded: yes, Screw locking, M23, Number of positions: 16, Type of contact: Male connector, Crimp connection, Flat gasket, 4x Ø3.2

The figure shows the 12-pos. product version



### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	26.050 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Data of the insulating body

Note	Order information: Order crimp contacts Ø 1 mm separately
Coding	N
Contact connection method	Crimp connection
Type of contacts	Male connector
Number of positions	16
Contact diameter of power contacts	1 mm
Nominal current per power contact at 25°C	8 A
Nominal voltage, power contact	150 V
Overvoltage category	II
Degree of pollution	3

#### Housing data

Housing material	Metal
------------------	-------

# Device connector, front mounting - RC-16P1N8A2300 - 1614959


## Technical data

### Housing data

Type of locking	Screw locking
Degree of protection (when plugged in)	IP67
Thread type	M23

## Drawings

Schematic diagram



## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440103
eCl@ss 9.0	27440102

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

## Device connector, front mounting - RC-16P1N8A2300 - 1614959

### Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

EAC B.01742
-------------

### Accessories

Accessories

Crimp contact

Crimp contact - RC-12P2000 - 1597862



Crimp contact, turned, Single contact, Contact diameter: 1 mm, Crimp range: 0.14 mm<sup>2</sup>...0.56 mm<sup>2</sup>

---

---