



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
6/14/13	C	UPDATED TITLE	T.B.	B.S.	
06/30/17	D	DIM. 151.42 WAS 149.20 DIM. 57.48 WAS 56.60	T.B.	B.S.	
12/28/20	E	Dim. 151.00 was 151.42	T.B.	B.S.	



MATERIAL:
 HOUSING: POLYPROPYLENE, BLACK
 FLAMMABILITY RATING -UL94 HB, UL FILE NO. E216959
 TEMPERATURE RANGE: -10°C to +100°C
 SPRINGS: SPRING STEEL, NICKEL PLATED
 RIVETS: BRASS, NICKEL PLATED
 LUGS: BRASS, NICKEL PLATED
 CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS
 PER EIA-540J000
 ROHS COMPLIANT

MOUNTING INSTRUCTION:
 USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD
 BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT.
 ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Inches)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal ±.5 (.020)		Scale	Drawn By B.S.
			Approved By T.B.
Fractional ± .8 (.030)	Title TEN "AA" CELL HOLDER WITH SOLDER LUGS		
Angular ± 3°	Date 12/28/20	Drawing Number BH10AAL	