



SCALANCE X310, managed plus IE switch, 3x 10/100/1000 Mbit/s and 7x 10/100 Mbit/s RJ45 ports LED diagnostics, error signaling Contact with select/set pushbutton, PROFINET IO device, network management, Integrated redundancy manager, office features (RSTP, VLAN, IGMP,...) C-plug in scope of supply.

<b>product type designation</b>	<b>SCALANCE X310</b>
<b>transfer rate</b>	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>interfaces / for communication / integrated</b>	
number of electrical connections	
• for network components or terminal equipment	10
number of 10/100 Mbit/s RJ45 ports / integrated	
• with securing collar	7
number of 10/100/1000 Mbit/s RJ45 ports / integrated	
• with securing collar	3
<b>interfaces / other</b>	
number of electrical connections	
• for signaling contact	1
• for power supply	1
type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
design of the removable storage	
• C-PLUG	Yes
<b>signal inputs/outputs</b>	
operating voltage / of the signaling contacts	
• at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
<b>supply voltage, current consumption, power loss</b>	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	No
<b>type of voltage / 1 / of the supply voltage</b>	DC
• supply voltage / 1 / rated value	24 V
• power loss [W] / 1 / rated value	9.6 W
• supply voltage / 1 / rated value	18 ... 32 V
• consumed current / 1 / maximum	0.4 A
• type of electrical connection / 1 / for power supply	4-pole terminal block
• product component / 1 / fusing at power supply input	Yes
<b>ambient conditions</b>	
ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +70 °C

<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity <ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP30
<b>design, dimensions and weights</b>	
design	compact
width	120 mm
height	125 mm
depth	123 mm
net weight	1.4 kg
fastening method	When used in shipbuilding, installation on a 35 mm standard mounting rail is not permitted.
<ul style="list-style-type: none"> <li>19-inch installation</li> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> <li>S7-300 rail mounting</li> <li>S7-1500 rail mounting</li> </ul>	No Yes Yes Yes No
<b>product features, product functions, product components / general</b>	
cascading in the case of a redundant ring / at reconfiguration time of <math>\lt;0.3\text{s}</math>	100
cascading in cases of star topology	any (depending only on signal propagation time)
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>CLI</li> <li>web-based management</li> <li>MIB support</li> <li>TRAPs via email</li> <li>configuration with STEP 7</li> <li>RMON</li> <li>port mirroring</li> <li>multiport mirroring</li> <li>CoS</li> <li>PROFINET IO diagnosis</li> </ul>	Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes
PROFINET conformity class	B
product function / switch-managed	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>Telnet</li> <li>HTTP</li> <li>HTTPS</li> <li>TFTP</li> <li>FTP</li> <li>BOOTP</li> <li>GMRP</li> <li>DCP</li> <li>LLDP</li> <li>SNMP v1</li> <li>SNMP v2</li> <li>SNMP v3</li> <li>IGMP (snooping/querier)</li> </ul>	Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes
identification & maintenance function	
<ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> <li>I&amp;M1 – higher level designation/location designation</li> </ul>	Yes Yes
<b>product functions / diagnostics</b>	
product function	
<ul style="list-style-type: none"> <li>port diagnostics</li> <li>statistics Packet Size</li> <li>statistics packet type</li> <li>error statistics</li> <li>SysLog</li> </ul>	Yes Yes Yes Yes Yes

product functions / VLAN	
product function	
<ul style="list-style-type: none"> <li>• VLAN - port based</li> <li>• VLAN - protocol-based</li> <li>• VLAN - IP-based</li> <li>• VLAN dynamic</li> </ul>	Yes No No Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
protocol / is supported / GVRP	Yes
product functions / DHCP	
product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> <li>• DHCP Option 82</li> <li>• DHCP Option 66</li> <li>• DHCP Option 67</li> </ul>	Yes Yes Yes Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> <li>• ring redundancy</li> <li>• High Speed Redundancy Protocol (HRP)</li> <li>• high speed redundancy protocol (HRP) with redundancy manager</li> <li>• high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes Yes Yes Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
<ul style="list-style-type: none"> <li>• media redundancy protocol (MRP) with redundancy manager</li> <li>• redundancy procedure STP</li> <li>• redundancy procedure RSTP</li> <li>• redundancy procedure MSTP</li> <li>• passive listening</li> </ul>	Yes Yes Yes Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• STP/RSTP</li> <li>• STP</li> <li>• RSTP</li> <li>• MSTP</li> <li>• RSTP big network support</li> <li>• LACP</li> </ul>	Yes Yes Yes Yes Yes Yes
product functions / security	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> <li>• ACL - port/MAC-based</li> <li>• IEEE 802.1x (radius)</li> <li>• broadcast/multicast/unicast limiter</li> <li>• broadcast blocking</li> </ul>	Yes Yes Yes Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
product functions / time	
product function	
<ul style="list-style-type: none"> <li>• SICLOCK support</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> <li>• SNTP</li> <li>• IEEE 1588 profile default</li> </ul>	Yes Yes No
standards, specifications, approvals	
standard	
<ul style="list-style-type: none"> <li>• for FM</li> <li>• for safety / from CSA and UL</li> </ul>	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 UL 60950-1, CSA C22.2 No. 60950-1

<ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	EN 61000-6-4:2007 (Class A) EN 61000-6-2:2005
MTBF	40 y
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul>	KF KFE
<b>standards, specifications, approvals / CE</b>	
certificate of suitability / CE marking	Yes
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
certificate of suitability	
<ul style="list-style-type: none"> <li>• CCC / for hazardous zone according to GB standard</li> </ul>	Yes
<b>standards, specifications, approvals / other</b>	
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
<ul style="list-style-type: none"> <li>• C-Tick</li> <li>• KC approval</li> <li>• railway application in accordance with EN 50155</li> </ul>	Yes Yes No
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• DNV GL</li> <li>• Korean Register of Shipping (KRS)</li> <li>• Polski Rejestr Statkow (PRS)</li> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>	Yes Yes No No Yes Yes Yes No
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)

last modified:

7/8/2022 