



Aerosusa.com
service@aerosusa.com
855.393.9905

RQB90-N



Plastic connector, quick-type, bend 90°, NPT outer thread, integrated snap-in sleeve with sealing, high density

Material: PA plastics

Temperature:

-40°C ... +120°C

-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Color: Black

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest outer dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

Note:

Lock-nuts and sealing washers sold separately. See below for corresponding accessories.

CERTIFICATIONS



"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Aerosusa.com
service@aerosusa.com
855.393.9905

Technical Data Sheet

| Product # | Part No. | Color | Trade Size | AD | Thread | I (in) | B (in) | C (in) | E (in) | F (in) | WS (in) | lb/100 | PU |
|--------------|--------------|-------|------------|------|--------|--------|--------|--------|--------|--------|---------|---------|-------|
| 5703.013.204 | 5703.013.204 | Black | 5/16" | 13 | 3/8" | 0.33 | 0.79 | 0.47 | 2.22 | 1.57 | 0.83 | 2.9101 | 50 PC |
| 5020.018.204 | 5020.018.204 | Black | 3/8" | 15.8 | 3/8" | 0.39 | 0.91 | 0.47 | 2.34 | 1.77 | 0.94 | 3.4172 | 50 PC |
| 5703.015.205 | 5703.015.205 | Black | 3/8" | 15.8 | 1/2" | 0.39 | 0.91 | 0.47 | 2.34 | 1.77 | 0.94 | 3.6817 | 50 PC |
| 5020.018.206 | 5020.018.206 | Black | 1/2" | 21.2 | 1/2" | 0.51 | 1.16 | 0.47 | 2.85 | 1.89 | 1.02 | 4.7840 | 50 PC |
| 5020.018.214 | 5020.018.214 | Black | 3/4" | 28.5 | 3/4" | 0.67 | 1.46 | 0.51 | 3.44 | 2.46 | 1.26 | 7.5178 | 25 PC |
| 5020.018.216 | 5020.018.216 | Black | 1" | 34.5 | 1" | 0.91 | 1.73 | 0.53 | 3.76 | 2.87 | 1.54 | 10.6924 | 10 PC |
| 5703.042.217 | 5703.042.217 | Black | 1 1/4" | 42.5 | 1 1/4" | 1.24 | 2.05 | 0.67 | 4.07 | 3.25 | 1.89 | 15.2119 | 10 PC |
| 5020.018.209 | 5020.018.209 | Black | 1 1/2" | 54.5 | 1 1/2" | 1.4 | 2.52 | 0.67 | 4.57 | 3.78 | 2.32 | 20.9218 | 5 PC |
| 5703.054.238 | 5703.054.238 | Black | 1 1/2" | 54.5 | 2" | 1.79 | 2.52 | 0.61 | 4.8 | 3.78 | 2.76 | 23.0603 | 5 PC |

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103