S41F1C-P05PJG0-650S

series_f, type_s4




General information

| Part number | S41F1C-P05PJG0-650S | |
|-------------------|---------------------|------------|
| Termination | crimp | |
| Size | 1 | CE MILES |
| Locking principle | push | C-FIME ETS |
| Coding | 1_halfshell | |
| Cable Diameter | cable_mini_65 | |
| Cable outlet | bend_relief | |







Contact insert description

| Number of contacts | 5 |
|--------------------|-----------|
| Contact type | pins |
| Contact diameter | 09mm |
| Insulator material | peek |
| Wire cross section | 22-26_awg |
| Termination | crimp |

reverse_gender_on_request

Technical information

| Max. creepage and air clearance distance | 10 _{_mm} | 07 _{_mm} |
|--|-------------------|-------------------|
| Nominal current single contact | 075 _a | iec_60512_5_2 |
| Nominal current insert | 5,625 A | vde_0298_4 |
| Test voltage | 135_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip68 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| Housing | m_chrome |
|---------|---------------|
| Contact | cu_alloy_gold |

safety_text_2 ul_text illustrative_text