

**Surge protection
SPD II 0 150V/50KA**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Type 2 spare arrester for the SPD series according to UL 1449 ed. 3. It is tested according to UL as type 4 for use in type 2 applications.

General ordering data

Order No.	1348330000
Type	SPD II 0 150V/50KA
Version	Surge protection, Low voltage, pluggable
GTIN (EAN)	4050118152753
Qty.	1 pc(s).

Surge protection SPD II 0 150V/50KA

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	18 mm	Height	45 mm
Depth	60 mm	Net weight	66 g

Temperatures

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

General data

Colour	Light Grey	Height with TS 35	74 mm
Lightning arrester	No	Optical function display	green = OK; red = arrester is defective - replace
Protection degree	IP 20	UL 94 flammability rating	V-0

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

technical data

Rated voltage (AC)	120 V	Highest continuous voltage (AC)	150 V
Total discharge current I_{total}	50 kA	Discharge current, max. (8/20 μ s)	40 kA
Protection level U_p (typ.)	≤ 1200 V	Colour	Light Grey
AC/DC/UC	AC	Response time	≤ 100 ns

Rated data UL

Test Voltage 39.1 (UL 1449)	240 V	UL certificate	E-File 354261 Type 2 by UL1449 Ed.3
-----------------------------	-------	----------------	-------------------------------------

Classifications

ETIM 3.0	EC000941	UNSPSC	30-21-19-21
eClass 5.1	27-13-08-01	eClass 6.2	27-13-08-02
eClass 7.1	27-14-02-01		

Approvals

ROHS	Conform
------	---------

Downloads

Declaration of Conformity	K481_05_12.pdf
---------------------------	--------------------------------