



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d ₁ Thread	Length l						d ₂	k
	6	8	10	16	20	-		
M 3	0.24	0.31	0.39	0.63	0.79	-	12 0.47	2.5 0.10
M 4	0.31	0.39	0.47	0.63	0.79	25 0.98	16 0.63	3.5 0.14
M 5	0.39	0.47	0.63	0.79	0.98	30 1.18	20 0.79	4 0.16
M 6	0.47	0.63	0.79	0.98	1.18	40 1.57	24 0.94	5 0.20
M 8	0.63	0.79	0.98	1.18	1.38	40 1.57	30 1.18	6 0.24
M 10	0.79	0.98	1.18	1.38	1.57	-	36 1.42	8 0.31

Specification

- Steel
 - Property class 5
 - Visible face fine turned
 - Blackened finish —
 - Zinc plated, blue passivated finish **ZB**
- Stainless steel AISI 303 **NI**
Matte shot-blasted finish
- *Strength Values of Screws* → page 2127
- *Stainless Steel Characteristics* → page 2143
- RoHS compliant

Information

DIN 653 flat knurled thumb screws are turned from solid bar. The thread of the screw extends up to the head and ends in a runout. They can be tightened and loosened quickly without tools.

see also...

- *Flat Knurled Thumb Screws GN 653.10 (Steel, with Brass / Plastic Tip)* → page 707
- *Flat Knurled Thumb Screws GN 653.2 (with Recessed Stud for Loss Protection)* → www.jwwinco.com
- *Knurled Thumb Screws DIN 464* → page 705

How to order (Steel, blackened finish) DIN 653-M8-35	1 Thread d ₁
	2 Length l
How to order (Steel, zinc plated) DIN 653-M3-8-ZB	1 Thread d ₁
	2 Length l
	3 Finish
How to order (Stainless steel) DIN 653-M5-20-NI	1 Thread d ₁
	2 Length l
	3 Material