SIEMENS

Data sheet

US2:52BP3GTUB

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 120V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Momentary 1 N.C.+1 N.C. Extra Late Break Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



	Enclosure	
number of command points 1		
delivery state as a kit No		
Actuator		
product extension optional light source Yes		
material of the actuating element plastic		
number of contact modules 2		
type of unlocking device without		
number of switching positions 3		
Front ring		
product component front ring Yes		
design of the front ring standard		
material of the front ring metal		
color of the front ring black		
Contact block/ lampholder		
number of lampholders 1		
Display		
number of LED modules 1		
General technical data		
product function positive opening No		
product component		
lamp transformer Yes		
light source Yes		
insulation voltage rated value 600 V		
type of voltage		
of the operating voltage AC		
of the input voltage AC		
surge voltage resistance rated value 4 kV		
protection class IP IP66		
• of the terminal IP20		
thermal current 10 A		
Supply voltage		
type of voltage of the supply voltage of the light source AC		
supply voltage of the light source at AC at 60 Hz		
• rated value 6 V		
Auxiliary circuit		
number of NC contacts for auxiliary contacts 2		
number of NO contacts for auxiliary contacts 0		
operational current at AC-15		
• at 110 V rated value 60 A		

 at 230 V rated value 	30 A		
• at 400 V rated value	15 A		
• at 500 V rated value	12 A		
Inputs/ Outputs			
output voltage 1 of the lamp transformer rated value	6 V		
Connections/ Terminals			
type of electrical connection	screw-type terminals		
tightening torque of the screws in the bracket	20 N·m		
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in		
Lamp			
color of the light source	yellow		
Ambient conditions			
ambient temperature			
during operation	-35 +70 °C		
during storage	-40 +85 °C		
Installation/ mounting/ dimensions			
shape of the installation opening	round		
Certificates/ approvals			
Further information			
Siemens has decided to exit the Russian market (see here).			
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business			
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an			
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).			
Information on the packaging			
https://support.industry.siemens.com/cs/ww/en/view/109813875			
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10			
Industry Mall (Online ordering system)			
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3GTUB			
Cax online generator			
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3GTUB			
Service&Support (Manuals, Certificates, Characteristics, FAQs,)			
https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3GTUB			
	Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)		
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3GTUB⟨=en			

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3GTUB&lang=en

last modified:

5/31/2021 🖸