



APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/1/22	
A		UPDATE SPEC.	11/30/22	JJ/RC



Ⓐ Lock Nut




Ⓑ Washer





Ⓔ Sealing Nut



Ⓒ Body



Ⓓ Seal



RECOMMENDED
 PANEL CUT-OUT
 (.173 [4.4] MAX PANEL THICKNESS)

SPECIFICATIONS:

Material:

Lock Nut: PA66, rated UL 94V-2

Body: PA66, rated UL 94V-2

Sealing Nut: PA66, rated UL 94V-2

Washer: Nitrile Butylene

Seal: Nitrile Butylene

Mechanical:

Cable Range (O.D.): 13-18mm

Thread O.D. L2: 28mm

Thread Length L2: 12mm

Spanner Size A&E: 35/33mm

Nut Torque: 3Nm Max.

Temperature Rating:

-40°C to +100°C

Environmental:

Waterproof: IP68

Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
 ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXX ± .015
.XXX ± .015	ØXXX ± .010

DRAWN	WX	11/1/22
CHECKED	RC	11/1/22
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY
 AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN
 PERMISSION FROM ADAM TECH

**ADAM
 TECH**

909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

TITLE
 WATERPROOF CONNECTOR, M28, 1 HOLE,
 CABLE GLAND, WATERPROOF: IP68

SIZE X	PART NO. CG-P-M28-1.5	REV. A
REF: S00211C	SCALE: NTS	SHEET 1 OF 1