



Ethernet Media converter Ha-VIS eCon 3011-ASFP

2-port Ethernet Media converter for vertical installation in control cabinets,
including 1 F.O. port (SFP)

Unmanaged	IP30	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
Number of ports, Copper / Termination	1x 10/100Base-T(X) / RJ45 (Twisted Pair) PoE support		
Number of ports, F.O. / Termination	1x 100Base-FX / SFP module slot		
mode PoE			
Input voltage / Termination	48 V DC		
Permissible range (min./max.)	46 V ... 57 V DC		
Input current	approx. 100 mA ... 400 mA at 48 V DC with PoE		
mode Non-PoE			
Input voltage / Termination	24 V DC / 5-pole, pluggable screw contact, redundant (PWR1 + / PWR1 - / PWR2 + / PWR2 - / FE)		
Permissible range (min./max.)	12 V ... 30 V DC		
Input current	approx. 100 mA (at 24 V DC)		
Housing material	metal, powder-coated		
Dimensions (W x H x D)	23 x 130 x 100 mm (without connectors)		
Weight	approx. 0.6 kg		
Working temperature	-40 °C ... +70 °C		
Approvals	cUL (in preparation)		
MTBF	2.090.000 h		

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS eCon 3011-ASFP Ethernet Switch with 1 RJ45 port 1 F.O. port	20 76 102 3101		
--	----------------	--	--

