


HC-M-PN3-4,00-BU-V

Order No.: 1663569

The illustration shows versions, pneumatic male, female and female with valve

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663569>Pneumatics female connector with valve, for HC-M-PN3 module, cross
section of hose 4.0 mm

Commercial data	
GTIN (EAN)	 4 017918 123376
sales group	D044
Pack	10 pcs.
Customs tariff	85366990
Catalog page information	Page 463 (PC-2009)

Product notesWEEE/RoHS-compliant since:
05/10/2006

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data	
Electrical characteristics	
Ambient temperature (operation)	-40 °C ... 125 °C
Mechanical characteristics	
Operating pressure, vacuum	6.00 bar
Internal diameter of pressure hose connection	4 mm
Insertion/withdrawal cycles	≥ 500
General characteristics	
Color	black

Material data

Contact material	Delrin acetal
------------------	---------------

Certificates / Approvals



Certification

GOST, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;