

**API 008** 8-pin socket  
**API 008FS** 8-pin finger-safe socket  
**API 011** 11-pin socket  
**API 011FS** 11-pin finger-safe socket  
**API CLP1** Hold-down spring. Works with sockets at left.  
**API BP4** 4-pin plug for APD series DIN housing

**8 and 11 Pin Sockets, Standard and Finger-Safe, Surface or DIN-Rail Mountable**

**ELECTRICAL RATING**

API 008 600 Volts, 10 Amps  
 API 008 FS, API 011, API 011 FS 300 Volts, 10 Amps

**CONSTRUCTION**

Contacts Brass, nickel plated  
 Screws Binder head, 6-32 x 1/4" steel zinc plated  
 Pressure clamp, 6-32 x 5/16" steel zinc plated  
 Wire size range #12 to #22 AWG solid or stranded  
 Screws, FS Box lug, M3 steel, nickel plated  
 Maximum wire gauge #14 AWG  
 Molding Black break-resistant thermoplastic

**AGENCY APPROVALS**

Standard Models	UL recognized	File No. E60008
FS models	UL recognized	File No. E113714
Standard Models	CSA certified	File No. LR29513
FS models	CSA certified	File No. LR26716
All Models	CE	

**SOCKETS**

**API 008**  
**API 008 FS**  
**API 011**  
**API 011 FS**


**DESCRIPTION**

8 Pin Octal  
 8 Pin Octal, Finger Safe  
 11 Pin Octal Style  
 11 Pin Octal Style, Finger Safe



API maintains a constant effort to upgrade and improve its products. Specifications are subject to change without notice. See api-usa.com for latest product information. Consult factory for your specific requirements.

**API Sockets API 008 and API 008 FS**



**API 011 and API 011 FS Sockets**

