



Illuminated mushroom pushbutton, 22 mm, round, plastic, green, 40mm, momentary contact type, with laser labeling, upper case and lower case, always upper case at the beginning of the word

|   |   |
|---|---|
| <b>product brand name</b>                                 | SIRIUS ACT  |
| <b>product designation</b>                                | Mushroom pushbuttons  |
| <b>design of the product</b>                              | Actuating/signaling element   |
| <b>product type designation</b>                           | 3SU1  |
| <b>product line</b>                                       | Plastic, black, 22 mm   |
| <b>Enclosure</b>  |   |
| <b>number of command points</b>                           | 1   |
| <b>Actuator</b>   |   |
| <b>design of the actuating element</b>                    | illuminated   |
| <b>principle of operation of the actuating element</b>    | momentary contact type  |
| <b>product extension optional light source</b>            | Yes   |
| <b>color of the actuating element</b>                     | green   |
| <b>material of the actuating element</b>                  | plastic   |
| <b>shape of the actuating element</b>                     | round   |
| <b>outer diameter of the actuating element</b>            | 40 mm   |
| <b>marking of the actuating element</b>                   | Customized labeling, text in lower case / capital letters, all words start with capital letters |
| <b>number of switching positions</b>                      | 2   |
| <b>Front ring</b>   |   |
| <b>product component front ring</b>                       | Yes   |
| <b>design of the front ring</b>                           | Standard  |
| <b>material of the front ring</b>                         | plastic   |
| <b>color of the front ring</b>                            | black   |
| <b>General technical data</b>                             |   |
| <b>product function</b>                                   |   |
| • EMERGENCY OFF function                                  | No  |
| • EMERGENCY STOP function                                 | No  |
| <b>protection class IP</b>                                | IP66, IP67, IP69(IP69K)   |
| <b>degree of protection NEMA rating</b>                   | 1, 2, 3, 3R, 4, 4X, 12, 13  |
| <b>shock resistance</b>                                   |   |
| • according to IEC 60068-2-27                             | sinusoidal half-wave 15g / 11 ms  |
| • for railway applications according to EN 61373          | Category 1, Class B   |
| <b>vibration resistance</b>                               |   |
| • according to IEC 60068-2-6                              | 10 ... 500 Hz: 5g   |
| • for railway applications according to EN 61373          | Category 1, Class B   |
| <b>operating frequency maximum</b>                        | 3 600 1/h   |
| <b>mechanical service life (switching cycles) typical</b> | 3 000 000   |
| <b>reference code according to IEC 81346-2</b>            | S   |
| <b>Substance Prohibitance (Date)</b>                      | 10/01/2014  |

| Ambient conditions   |  |
|--|--|
| <b>ambient temperature</b>   |  |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul> | -25 ... +70 °C<br>-40 ... +80 °C                                   |
| environmental category during operation according to IEC 60721                             | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions   |  |
| <b>height</b>  | 40 mm  |
| <b>width</b>   | 40 mm  |
| <b>shape of the installation opening</b>   | round  |
| <b>mounting diameter</b>   | 22.3 mm  |
| <b>positive tolerance of installation diameter</b>   | 0.4 mm   |
| <b>mounting height</b>   | 27.5 mm  |
| <b>installation width</b>  | 40 mm  |
| <b>installation depth</b>  | 24.4 mm  |
| Certificates/ approvals  |  |
| Further information  |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-1BD40-0AA0-Z Y15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-1BD40-0AA0-Z Y15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-1BD40-0AA0-Z Y15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1001-1BD40-0AA0-Z Y15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-1BD40-0AA0-Z Y15&lang=en)

last modified:

1/27/2022 