



Inch table

Dimensions in: inches - millimeters

Length L	d Standard material (PP)	a	b	h	t min.
3.39 ±0.02 86 ±0.5	1/4 x 20	0.55 14	0.91 23	1.73 44	0.47 12
4.61 ±0.02 117 ±0.5	5/16 x 18	0.59 15	0.98 25	1.93 49	0.51 13
5.20 ±0.02 132 ±0.5	5/16 x 18	0.63 16	1.02 26	2.13 54	0.51 13
5.91 ±0.04 150 ±1	5/16 x 18	0.63 16	1.06 27	2.20 56	0.51 13
7.05 ±0.04 179 ±1	5/16 x 18	0.63 16	1.06 27	2.24 57	0.51 13

Metric table

Dimensions in: millimeters - inches

Length L	d Standard material (PP)						a	b	h	t min.				
	M 5	M 6	-	-	HT material (PA) M 6	-				M4	M5	M6	M8	M10
86 ±0.5 3.39 ±0.02	M 5	M 6	-	-	M 6	-	14 0.55	23 0.91	44 1.73	-	10 0.39	12 0.47	-	-
94 ±0.5 3.70 ±0.02	M 5	M 6	-	-	-	-	14 0.55	24 0.94	48 1.89	-	10 0.39	12 0.47	-	-
117 ±0.5 4.61 ±0.02	M 4	M 5	M 6	M 8	M 6	M 8	15 0.59	25 0.98	49 1.93	10 0.39	10 0.39	12 0.47	13 0.51	-
120 ±0.5 4.72 ±0.02	M 5	M 6	M 8	-	-	-	15 0.59	25 0.98	49 1.93	-	10 0.39	12 0.47	13 0.51	-
132 ±0.5 5.20 ±0.02	M 5	M 6	M 8	-	-	-	16 0.63	26 1.02	54 2.13	-	10 0.39	12 0.47	13 0.51	-
150 ±1 5.91 ±0.04	M 6	M 8	M 10	-	-	-	16 0.63	27 1.06	56 2.20	-	-	12 0.47	13 0.51	17 0.67
160 ±1 6.30 ±0.04	M 6	M 8	M 10	-	-	-	16 0.63	27 1.06	55 2.17	-	-	12 0.47	13 0.51	17 0.67
179 ±1 7.05 ±0.04	M 8	M 10	-	-	M 8	-	16 0.63	27 1.06	57 2.24	-	-	-	13 0.51	17 0.67
235 ±1 9.25 ±0.04	M 8	M 10	-	-	-	-	18.5 0.73	29 1.14	61 2.40	-	-	-	13 0.51	17 0.67
300 ±1 11.81 ±0.04	M 10	-	-	-	-	-	22 0.87	32 1.26	64 2.52	-	-	-	-	17 0.67

Specification

- Technopolymer plastic (Polypropylene PP) —
 - Shock-resistant
 - Temperature resistant up to 212 °F (100 °C)
 - Black, matte finish

- Technopolymer plastic (Polyamide PA) **HT**
 - Glass fiber reinforced
 - Temperature resistant up to 390 °F (200 °C)
 - Black-gray, matte finish

- Tapped inserts
Brass

• Strength Values

• Plastic Characteristics

• RoHS compliant

Information

EN 725 cabinet "U" handles are well known for their smooth ergonomically shaped elliptical design. High impact strength. Resistant to solvents, oils, grease and other chemical agents.

On request

- Various metric and inch size fasteners and kit packaging

How to order (Inch, up to 212 °F (100 °C))	1 Length L
EN 725-132-5/16X18	2 Thread d

How to order (Metric, up to 390 °F (200 °C))	1 Length L
EN 725-86-M6-HT	2 Thread d
	3 Material