1-1926720-6 V ACTIVE

MINIPAK

TE Internal #: 1-1926720-6


Rectangular Power Connectors, Header, Plug, Board-to-Board, 87 Position, 2.75 mm [.108 in / .079 in] Centerline, Printed Circuit

Board, UL 94V-0

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Board-to-Board

Number of Positions: 87

Centerline (Pitch): 2.75 mm [.079 in, .108 in]

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Mating & Unmating Configuration	Make First / Break Last
Number of Positions	87
PCB Mount Orientation	Right Angle
Number of Power Positions	6, 12
Number of Signal Positions	15
Number of Rows	5
Board-to-Board Configuration	Co-Planar

Electrical Characteristics

Insulation Resistance	1000 MΩ
Operating Voltage	250 VDC

Body Features



Contact Features	
PCB Contact Termination Area Plating Material Thickness	.5 μm[19.685 μin][20 μin]
Contact Layout	Matrix
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material	Gold
Contact Shape & Form	Single Beam
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy, Phosphor Bronze
Contact Current Rating (Max)	16 A
Contact Retention Within Housing	With
Contact Type	Blade, Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
ermination Features	
Termination Post & Tail Length	3.3 mm[.13 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit, Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment Type	Boardlock
Mating Alignment Type	Passive Guide
Mating Retention	Without
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
	Board Mount
Connector Mounting Type	
Connector Mounting Type lousing Features	
	2.75 mm[.079 in][.108 in]
lousing Features	2.75 mm[.079 in][.108 in] Black
lousing Features Centerline (Pitch)	
lousing Features Centerline (Pitch) Housing Color	Black



PCB Thickness (Recommended)	.06 mm[1.4 in]
Product Width	26.5 mm[1.043 in]
Product Length	55.12 mm[2.17 in]
Row-to-Row Spacing	2 mm[.079 in]
Usage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
CSA Rating	Certified
UL Rating	Recognized
Agency/Standard	CSA, UL
Agency/Standard Approved Standards	CSA, UL UL E28476
Approved Standards	UL E28476
Approved Standards UL Flammability Rating	UL 94V-0
Approved Standards UL Flammability Rating Glow Wire Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability
Product Compliance Disclaimer	

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Customers Also Bought













Documents

Product Drawings

AssyMinipakHDL6p15s6PRAPlugbrdlock

English

CAD Files

Customer View Model



ENG_CVM_CVM_1-1926720-6_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1926720-6_C.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-1926720-6_C.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

POWER_CONNECTORS_CATALOG_SEC01_BOARD_TO_BOARD

English

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

8-1773448-5 MINIPAK HDL Connectors Datasheet

English

8-1773448-5 MINIPAK HDL Connectors Datasheet

English

Product Specifications

Application Specification

English