

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
FT	0				
	D3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

Diagram showing the front view of the connector shell. The outer diameter is labeled as $.975 \text{ MAX DIA}$. The mating face is indicated. Four contact cavities are numbered 1, 2, 3, and 4. Dimensions for the cavities are: 1: $.110$, 2: $.000$, 3: $.110$, 4: $.110$. A note states: "AMP PART NO THIS SURFACE".

Diagram showing the side view of the coupling ring. The length is labeled as 1.365 MAX . The material is specified as "GLASS FILLED NYLON, 6/6, BLACK". A note states: "COUPLING RING MATERIAL: SEE TABLE".

- CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.
- THIS CONNECTOR WILL ACCEPT FOUR (4) MULTIMATE PIN CONTACTS.

3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

3 OBSOLETE	DIE CAST ZINC	206429-2
	POLYESTER, BLACK	206429-1
	COUPLING RING MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	S.RIDGLEY	BG	8/2/90	TE TE Connectivity	
DIMENSIONS: INCHES		CHK	R.STONE		04/26/91		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		-		NAME	
0 PLC ± -		PRODUCT SPEC		-		PLUG ASSEMBLY, SHELL	
1 PLC ± -		APPLICATION SPEC		-		SIZE 11, REVERSE SEX,	
2 PLC ± -		WEIGHT		-		SERIES 1, CPC	
3 PLC ± -		SCALE		2:1		RESTRICTED TO	
4 PLC ± -		SHEET		1 of 1		-	
ANGLES ± -		CUSTOMER DRAWING		A2 00779 C=206429		REV D3	
FINISH		-		-		-	

1471-9 (3/11)

206429

B

A