

# UL Type AWM

90°C 1000 Volts UL Listed

**Product Construction:**


**Conductor:**

- 14 AWG fully annealed stranded bare copper per ASTM B-8

**Insulation:**

- Premium-grade, color-coded PVC
- Temperature range: -20°C to +90°C
- Color code: See chart below

**Jacket Marking:**

- CAROL (SIZE) 90°C 1000V  AWM

**Applications:**

- Motor and transformer lead
- External wiring of machinery

**Features:**

- Outstanding oil, flame and moisture resistance
- Extra-flexible

**Industry Approvals:**

- UL Type AWM

**Packaging:**

- 500' (152.4 m) spools
- Other put-ups available on special order



**AWM - 1000 VOLT - UL**

CATALOG NUMBER	AWG SIZE	COND. STRAND	NOMINAL INS. THICKNESS		NOMINAL O.D.		STOCK COLORS	APPROX. NET WT. LBS/M <sup>(6)</sup>
			INCHES	mm	INCHES	mm		
76422*	14	19/0147	0.032	0.81	0.138	3.51	1-8	20

<sup>(6)</sup> Actual shipping weight may vary.  
 \* Non-stock item; minimum quantity purchase required.

**COLOR CODE CHART**

STOCK COLORS	ORDERING SUFFIX	STOCK COLORS	ORDERING SUFFIX
Black	01	Green	06
White	02	Yellow	05
Red	03	Orange	04
Blue	07	Brown	08