36 INCHES LENGTH






Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

Connector B

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



Part #:	112234	Part #:	RG-174	Part #:	132245
Description:	BNC Clamp BHD JK RG188 50O	Description:	RG-174 - PE 0.1	Description:	SMA R/A BHD JK RG174 RG316 LMR100
Type:	BNC	Dielectric:	PE		500
Gender:	Jack	Shielding:	Braid	Туре:	SMA
Body Type:	Straight	Diameter:	0.1	Gender:	Jack
Contact Type:	Crimp	Impedance:	50 Ohm	Body Type:	Right Angle
Polarity:	Standard	Sheathing:	None	Contact Type:	Solder
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Polarity:	Standard
Mounting:	Bulkhead - Rear Mount	Length:	36 Inches	Impedance:	50 Ohm
Body Material:	Brass			Mounting:	Bulkhead - Rear Mount
Body Finish:	Nickel			Body Material:	Brass
IP Rating:	None			Body Finish:	Gold
Contact Material:	Beryllium Copper			IP Rating:	None
Contact Finish:	Silver			Contact Material:	Beryllium Copper
Max. Freq.:	4 GHz			Contact Finish:	Gold
Booting:	BNC Jack Straight BHD			Max. Freq.:	12.4 GHz
Ū	•			Booting:	SMA Jack Right Angle
				Clocking:	0°

Cable



CONTROLLED DOCUMENT - DO NOT COPY

Connector A

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:

BNC-ST-JK/SMA-RA-JK G174 36I

Part No

Q-0402P0003036i

UNLESS SPECIFIED TOLERANCE:

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: TER LABEL IF LEN

CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES