

wire connector CU with control wire voltage tap-off 3 units accessory for:  
3VA6 150/250



Model	
product brand name	SETRON
product designation	accessories
Product version	circular conductor terminal
Accessories	Wire connector
General technical data	
designation / of the terminal	TC1.3
Connections according IEC	
stripped length	18 mm
Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	90 °C
stripped length	0.7 in
connectable conductor cross-section	
<ul style="list-style-type: none"> <li>• for copper cable / solid / minimum</li> <li>• for copper cable / solid / maximum</li> <li>• for copper cable / stranded / minimum</li> <li>• for copper cable / stranded / maximum</li> <li>• for copper cable / finely stranded / minimum</li> <li>• for copper cable / finely stranded / maximum</li> </ul>	14 AWG 10 AWG 14 AWG 1/0 AWG 14 AWG 1/0 AWG
tightening torque / when using copper cables	
<ul style="list-style-type: none"> <li>• solid</li> <li>• stranded</li> <li>• finely stranded</li> </ul>	14 - 10 AWG: 55 lb-in 14 - 8 AWG: 55.0 lb-in 6 - 2 AWG: 75 lb-in 1 AWG - 1/0: 120 lb-in 14 - 8 AWG: 55.0 lb-in 6 - 2 AWG: 75 lb-in 1 AWG - 1/0: 120 lb-in

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9143-0JK11>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9143-0JK11>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9143-0JK11](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9143-0JK11)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/5/2022

