



- △ 2.54um[.000100] MIN TIN-LEAD OVER 1.27um[.000050] MIN NICKEL.
- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 6.35[.250] FROM MATING END WITH GOLD FLASH ON REMAINDER, ALL OVER 1.27um[.000050] MIN NICKEL.
- △ POSTS ARE SEMI-AUTOMATICALLY WIREABLE AND WILL ACCOMODATE (SEE TABLE) TERMINATIONS.
- 4. #24 AWG MAX WIRE TO BE USED WITH THIS CONNECTOR.
- △ AMP, PART NUMBER, DATE CODE & THE LETTER P INK STAMPED IN THIS AREA.
- △ 2.54um[.000100] MIN TIN OVER 1.27um[.000050] MIN NICKEL.

△	6.63 [.261]	1	3-205317-5
△	16.74 [.659]	3	3-205317-4
△	6.63 [.261]	1	3-205317-1
△	16.74 [.659]	3	205317-1
POST PLATING	A	NO OF TERM	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN C. REIFSNYDER 08 FEB 96	APVD R. STONE 22 FEB 96	TYCO Electronics Tyco Electronics Corporation Harrisburg, Pa 17105-3608
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± 0.13 [.005]	NAME W. MCALONIS 22 FEB 96
4 PLC ± -	ANGLES ± -	FINISH SEE CALLOUTS	WEIGHT -	SIZE A1
MATERIAL SEE CALLOUTS	FINISH SEE CALLOUTS	SCALE 4:1	SHEET 1 OF 1	REV V

PIN ASSY, 14 POSITION, AUTOWIREABLE, STANDARD M SERIES
 00779 ©=205317
 CUSTOMER DRAWING