

SCSI- and Computer Cable Tester



This SCSI tester can test cable with up to 68 lines. With the optional PC or MAC cable Test Unit it can be upgraded to a multi cable tester. The transmitted and received data between the two ends of the cable will be compared. The result is shown by LEDs.

- SCSI tester with 2 x D-SUB 50-pin HP and 2 x D-SUB 68-pin HP female
- using adaptors all SCSI cable can be tested
- checks: pass-through, pin-assignment and shielding
- selectable test speed, manual + automatic test run
- LEDs: 2 x 68 for each line, 2 x shielding, 1 x battery, 6 x number of lines
- buttons: 1 x reset, 1 x test, 1 x test speed, 1 x number of lines, 1 x ON/OFF
- power supplied by 9 V Block battery, 9 V / 500 mA external power supply optional
- dimensions (WxDxH/mm) 180 x 131 x 40, weight 550 gr
- delivery incl. artificial leather bag

ACT-SCSI

SCSI Cable Tester

Flat Ribbon Cable Tester

With this tester 10- / 26- / 34- / 40- / 50-wire flat ribbon cable can be tested. The PC (ACT-PC) and MAC (ACT-MAC) cable Test Units can also be connected to this tester. Pin allocation is shown on a LC-Display.



- checks: pass-through, pin-assignment and shielding
- an integrated CPU stores the pin assignments, ideal for mass production testing purpose
- backlighted LCD Display
- connectors input: IDC 50/ IDC 40/ IDC 34/ IDC 26/ IDC 10/ D-SUB 15 male, D-SUB 9 female
- connectors output: IDC 50/ IDC 40/ IDC 34/ IDC 26/ IDC 10/ D-SUB 15 male, D-SUB 9 female
- 4 buttons: read, test, up, down
- dimensions (WxDxH/mm) 250 x 134 x 35, weight 800 gr
- delivery incl. artificial leather bag
- power supplied by 9 V Block battery, 9 V / 500 mA external power supply optional

ACT-FLAT

Flat Ribbon Cable Tester

PC Cable Test Unit

Can only be operated connected to SCSI or Flat Ribbon Cable Tester! Tests all suitable PC cable, as well as USB, Chinch, Coax, TP, DIN and MiniDIN cable.

- connectors: 2 x female and 2 x male: D-SUB 9, D-SUB 15, D-SUB 25, D-SUB 15 HD, CENT 36
2 x female: DIN 5, MiniDIN 4, USB A, MiniDIN 6, BNC, RCA, RJ45, Chinch
- dimensions (WxDxH/mm): 250 x 130 x 35, weight 750 gr
- delivery incl. bag, 2 x IDC Flat Ribbon Cable, DIN 5 + MiniDIN 6 M/M adaptor cable



ACT-PC
ACT-MAC

PC Cable Test Unit
MAC Cable Test Unit

MAC Cable Test Unit

Can only be operated connected to SCSI or Flat Ribbon Cable tester! Tests all suitable cable for Apple Macintosh computers.

- connectors: 2 x female: MiniDIN 8, MiniDIN 4, D-SUB 25, BNC, RJ45, RCA, Chinch
1 x female: D-SUB 9, D-SUB 25, DIN 5, HDI 30, 1 x male: D-SUB 9, D-SUB 15
- dimensions (WxDxH/mm): 250 x 130 x 35, weight 750 Gramm
- delivery incl. bag, 2 x IDC Flat Ribbon Cable, DIN 5 + MiniDIN 6 M/M adaptor cable

PC Cable Tester, Standalone

With this tester all suitable PC cable can be tested.



- checks: pass-through, pin-assignment and shielding
- pin allocation shown by LEDs
- LEDs: 25 x transmit, 36 x receive, 1 x battery, 2 x shielding, 4 x number of wires
- 4 buttons: test, auto / manuell, speed, ON/OFF
- automatic and manual test run
- connectors: D-SUB 9 M/F, D-SUB 15 M/F, D-SUB 15 HD M/F, D-SUB 25 M/F, CENT 36 female, BNC male, RJ45 female, USB A+B female, IEEE 1394 female
- power supply by 9 V Block battery, 9 V / 150 mA external power supply optional
- dimensions (WxDxH/mm): 250 x 130 x 35

ACT-PC-SO

PC Cable Tester, Standalone