0.25 METER LENGTH



Connector A 901-9872 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 172180 N-Type Plug Right Angle Brass White Bronze + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector B		Connector A			Cable		Connector B		
B0° 135° 225 270° 315° Connector A	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	901-9872 SMA R/A PLUG RG174 50O SMA Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold None Brass Gold 12.4 GHz SMA Plug Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 0.25 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	172180 N-Type R/A PLUG R N-Type Plug Right Angle Solder Standard 50 Ohm Cable Brass White Bronze None Brass Gold 11 GHz N-Type Plug Right A 0°	2G174 RG316 LMR100 500	
			THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-RA-PL/N-RA-PL G174 0.25M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	