

60 INCHES LENGTH



Connector A
132245
SMA Jack Right Angle
Bulkhead - Rear Mount Brass Gold + Heatshrink

50 Ohm RG-174
Continuity/Hi-Pot

Connector B
132117RP
SMA Jack Straight
Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
Part #:	132245	Part #:	RG-174	Part #:	132117RP
Description:	SMA R/A BHD JK RG174 RG316 LMR100 500	Description:	RG-174 - PE 0.1	Description:	SMA JACK RP RG316 500
Type:	SMA	Dielectric:	PE	Type:	SMA
Gender:	Jack	Shielding:	Braid	Gender:	Jack
Body Type:	Right Angle	Diameter:	0.1	Body Type:	Straight
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Crimp
Polarity:	Standard	Sheathing:	None	Polarity:	Reverse
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount	Length:	60 Inches	Mounting:	Cable
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Gold
IP Rating:	None			IP Rating:	None
Contact Material:	Beryllium Copper			Contact Material:	Brass
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	12.4 GHz			Max. Freq.:	12.4 GHz
Booting:	SMA Jack Right Angle			Booting:	SMA Jack Straight RP
				Clocking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-RA-JK/SMA-ST-JK-RP G174 60I

Part No:
Q-2P0710003060I

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES