

SPECIFICATION CONTROL DRAWING			7528A1422
CHEMINAX	75 OHM, AWG 28, 7 STRANDS OF AWG 36, COAXIAL CABLE	Date	12-5-13
		Revision	A
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
CONSTRUCTION DETAILS		ELECTRICAL CHARACTERISTICS	
DIMENSIONS ARE NOMINAL VALUES IN INCHES, UNLESS OTHERWISE DESIGNATED. 		CHARACTERISTIC IMPEDANCE 75 ± 3 ohms, Method B CAPACITANCE 17.6 pF/ft. (nominal) VELOCITY OF PROPAGATION 77% (nominal)	
		ADDITIONAL REQUIREMENTS	
		<u>ELECTRICAL</u>	
		CONDUCTOR RESISTANCE	62.0 ohms/1000 ft. (nominal)
		INSULATION RESISTANCE	10,000 megohms (minimum) for 1000 ft.
		JACKET FLAWS	
		SPARK TEST	1.0 kV (rms)
		IMPULSE TEST	6.0 kV (peak)
		VOLTAGE WITHSTAND (DIELECTRIC)	1500 volts (rms)
		<u>ENVIRONMENTAL</u>	
		FLAMMABILITY	Method B
		HEAT SHOCK	225°C
		LOW TEMPERATURE-COLD BEND	-55°C/3.00 inch mandrel
		VOLTAGE WITHSTAND (Post Environmental)	1000 volts (rms), 1 minute
		<u>PHYSICAL</u>	
		INSULATION (DIELECTRIC)	
		ELONGATION	50% (minimum)
		TENSILE STRENGTH	600 lbf/in ² (minimum)
		JACKET	
		ELONGATION	200% (minimum)
		TENSILE STRENGTH	2000 lbf/in ² (minimum)
		JACKET THICKNESS	.012 inch (nominal)
		SHIELD COVERAGE	90% (minimum)
		WEIGHT	9.7 lbs/1000 ft. (nominal)
Outer jacket color will be translucent white (designated by a "-9X" appended to the part number, e.g. 7528A1422-9X), unless otherwise specified.		<u>ENGINEERING REFERENCE</u>	
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.		MAX TEMPERATURE RATING	200°C continuous conductor temperature
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
Page 1 of 1	Rayfoam, Cheminax, Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		



Raychem Wire & Cable
 501 Oaks Avenue
 Redwood City, California 94063-3800
 Ph. 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.