	12	11	10	9	8	7	6		
	MATERIAL NO.	ENGINEERING NO.	FINISHED LEN	GTH C	CABLE LENGTH TOLERANCES <.3M [1FT]: +19mm-0 [+.75in-0]				
	1300240028	DN01A-M010	1 M (3 FT 3.37	IN)					
н	1300240031	DN01A-M020	2 M (6 FT 6.74	IN)					
	1300240034	DN01A-M050	5 M (16 FT 4.8	5 IN)	.39M [1 - 3FT]: +44.5mm-0 [+1.75in-0]				
					-	T]: +55.6mm-0 [+2 2FT: +88.9mm-0 [+	-		
					3.7 - 7.3M [12 - 2	24FT]: +165.1mm-	0 [+6.50in-0]		
					7.3-14.6M [24 - 4	48FT]: +317.5mm-	0 [+12.50in-0]		
					14.6 - 30.5M [48	-100FT]: +622.3m	m-0 [+24.50in-0]		
					OVER 30M [100	FT] +2% OF FINIS	SHED LENGTH		
G									

3

P1


(2)

2.25

4

57.2

BRADHARRISON



MALE FACE VIEW

NOTES:

С

В

- 1. MATERIAL: AS NOTED
- 2. FINISH: AS NOTED
- 3. ELECTRICAL: VOLTAGE RATING: 300V CURRENT: 4A
- 4. TEMP RATING: -20°C TO +80°C C
- 5. PROTECTION: IP67 (WHEN MATED) C
- 6. CSA CERTIFIED FILE: LR6837 . CSA CERTIFIED FILE: LR6837 UL RECOGNIZED FILE: E152210
- 7. COUPLING THREAD: 7/8"-16UN
- 8. MATES WITH: MINI-CHANGE, A-SIZE 5 POLE RECEPTACLE
- 9. ALL DIMS ARE FOR REFERENCE UNLESS
- TOLERANCED OR NOTED OTHERWISE

6	WRAP LABEL					L	BLACK/YEL	BLACK/YELLOW	
5	OVERMOLD				TPE		GRAY	GRAY	
4	COUPLING NUT			ZINC DIE CAST		BLACK E-C	BLACK E-COAT		
3	PIN CONTACT				Cu ALLOY		GOLD OVE	GOLD OVER NICKEL	
2	MALE INSERT				TPE		BLACK	BLACK	
1	CABLE, DEV-NET, TRUNK, #18-2, 15-2				PVC JACKET		GRAY	GRAY	
ITEM	DESCRIPTION				MATERIAL		FINISH	FINISH	
DOCUM	IENT STATUS	P1	RELEASE DATE	2022/03/26	00:25:17	7			
FORMAT: Eng-lega-master-tb-pro REVISION: E1 DATE: 2021/05/01	^{∞⊷} 12		11	10		9	8		

6

5

Δ

