

XCSLE3737512

Safety switch, Telemecanique Safety switches XCS, plastic XCSLE, 4NC+2 NO, slow break, 3 entries tapped M20, 24 V



Main

| | |
|--|--|
| Range of Product | Telemecanique Safety switches XCS |
| Product or Component Type | Safety switch |
| Component name | XCSLE |
| Design | Slim |
| Material | Plastic |
| Head type | Key operated turret head |
| Contacts type and composition | 2 NC + 1 NO |
| Contact operation | Slow-break, break before make |
| Solenoid contacts type and composition | 2 NC + 1 NO slow-break, break before make) |
| Cable entry | 3 entries tapped M20 x 1.5 |
| Electromagnet interlocking | Locking on energisation and unlocking on de-energisation of solenoid |
| [Us] solenoid rated supply voltage | 24 V |
| Cable outer diameter | 0.28...0.51 in (7...13 mm) |
| Electrical connection | Spring terminal 1 x 1.5 mm ² flexible or solid cable Spring terminal 2 x 0.5 mm ² flexible cables with 13 mm bared ends |
| Number of poles | 3 |
| Locking options description | With interlocking, locking by solenoid |
| Local signalling | For actuator withdrawn 1 LED (orange) For actuator inserted and locked 1 LED (green) |
| Signalling circuit voltage | 24 V |

Complementary

| | |
|--|---|
| Insulation | Double insulated |
| Positive opening | With NC contact |
| Supply voltage type | AC/DC |
| Supply frequency | 50/60 Hz |
| Load factor | 1 |
| Signalling circuit type | AC/DC |
| Mechanical durability | 1000000 cycles |
| Minimum actuation speed | 0.03 ft/s (0.01 m/s) |
| Maximum actuation speed | 1.64 ft/s (0.5 m/s) |
| [Ie] rated operational current | 0.55 A 24 V, DC-13, R300 EN/IEC 60947-5-1 0.75 A 240 V, AC-15, C300 EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 4 A |
| Maximum load current | <= 15 A |
| [Ui] rated insulation voltage | 300 VUL 508 300 VCSA C22.2 No 14 250 V 3)EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 4 kV EN/IEC 60947-5-1 |
| Minimum switching current | 10 mA at 20 °C |
| Minimum switching voltage | 17 V |
| Short-circuit protection | 4 A cartridge fuse gG (gl) 6 A fast blow |

| | |
|--|--|
| Maximum actuator forcible withdrawal rtc | 1400 N |
| Minimum actuator force for extraction | 20 N |
| Resistance to mechanical impact | 1.2 J against the partition 4.9 J without partition |
| Maximum operating rate | 10 cyc/mn for maximum durability |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach SIL 3 EN/IEC 61508 |
| Safety reliability data | B10d = 5500000 value given for a life time of 20 years limited by mechanical or contact wear |
| Body Material | PA (polyamide) |
| Head material | PA (polyamide) |
| Depth | 2.01 in (51 mm) |
| Height | 8.07 in (205 mm) |
| Width | 1.73 in (44 mm) |
| Net Weight | 1.17 lb(US) (0.53 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | UL 508 EN 1088/ISO 14119 EN/IEC 60947-5-1 EN/ISO 13849-1 EN/IEC 62061 CSA C22.2 No 14 EN/IEC 60204-1 |
| Product Certifications | TÜV UL CSA |
| Protective treatment | TC |
| Ambient Air Temperature for Operation | -13...140 °F (-25...60 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 5 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 10 gn 11 ms IEC 60068-2-27 |
| Electrical shock protection class | Class II EN/IEC 61140 |
| IP degree of protection | IP66 conforming to EN/IEC 60529 and EN/IEC 60947-5-1 IP67 |

Ordering and shipping details




| | |
|-----------------------|-------------------------------|
| Category | 22411-LIMIT SWITCHES,IEC,XCKJ |
| Discount Schedule | T |
| GTIN | 3606480671616 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 22.22 oz (630.0 g) |
| Returnability | No |
| Country of origin | ID |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 2.24 in (5.7 cm) |
| Package 1 width | 2.95 in (7.5 cm) |
| Package 1 Length | 9.06 in (23 cm) |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 128 |
| Package 2 Weight | 177.78 lb(US) (80.64 kg) |
| Package 2 Height | 27.56 in (70 cm) |
| Package 2 width | 23.62 in (60 cm) |
| Package 2 Length | 31.50 in (80 cm) |
| Unit Type of Package 3 | S02 |

| | |
|------------------------------|------------------------|
| Number of Units in Package 3 | 8 |
| Package 3 Weight | 11.11 lb(US) (5.04 kg) |
| Package 3 Height | 5.91 in (15 cm) |
| Package 3 width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |