

DM74S299 3-STATE 8-Bit Universal Shift/Storage Registers

General Description


This Schottky TTL eight-bit universal register features multiplexed inputs/outputs to achieve full eight bit data handling in a single 20-pin package. Two function-select inputs and two output-control inputs can be used to choose the modes of operation listed in the function table.

Synchronous parallel loading is accomplished by taking both function-select lines, S0 and S1, high. This places the 3-STATE outputs in a high-impedance state, which permits data that is applied on the input/output lines to be clocked into the register. Reading out of the register can be accomplished while the outputs are enabled in any mode. A direct overriding input is provided to clear the register whether the outputs are enabled or off.

Features

- Multiplexed inputs/outputs provide improved bit density
- Four modes of operation:
Hold (Store) Shift Left
Shift Right Load Data
- 3-STATE outputs drive bus lines directly
- Can be cascaded for N-bit word lengths
- Operates with outputs enabled or at high Z
- Guaranteed shift (clock) frequency 50 MHz
- Typical power dissipation 700 mW

Connection Diagram



Order Number DM74S299N
See Package Number N20A

Absolute Maximum Ratings (Note 1)

Supply Voltage
Input Voltage

7V
5.5V

Operating Free Air Temperature Range

DM74S
Storage Temperature Range

0°C to +70°C
-65°C to +150°C

Recommended Operating Conditions

(See Section 1 for Test Waveforms and Output Load)

| Symbol | Parameter | DM74S299 | | | Units |
|------------------|---|------------|-----|------|-------|
| | | Min | Nom | Max | |
| V _{CC} | Supply Voltage | 4.75 | 5 | 5.25 | V |
| V _{IH} | High Level Input Voltage | 2 | | | V |
| V _{IL} | Low Level Input Voltage | | | 0.8 | V |
| I _{OH} | High Level Output Current (Q _A thru Q _H) | | | -6.5 | mA |
| | High Level Output Current (Q _A , Q _H) | | | -0.5 | |
| I _{OL} | Low Level Output Current (Q _A thru Q _H) | | | 20 | mA |
| | High Level Output Current (Q _A , Q _H) | | | 6 | |
| f _{CLK} | Clock Frequency (Note 3) | 0 | 70 | 50 | MHz |
| f _{CLK} | Clock Frequency (Note 4) | 0 | 60 | 40 | MHz |
| t _w | Pulse Width (Note 6) | Clock High | 10 | | ns |
| | | Clock Low | 10 | | |
| | | Clear Low | 10 | | |
| t _{su} | Setup Time (Notes 5, 6) | Select | 15↑ | | ns |
| | | Data High | 7↑ | | |
| | | Data Low | 5↑ | | |
| t _H | Hold Time (Notes 5, 6) | 5↑ | | | ns |
| t _{REL} | Clear Release Time (Note 6) | 10↑ | | | ns |
| T _A | Free Air Operating Temperature | 0 | | 70 | °C |

Note 1: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: The symbol (↑) indicates the rising edge of the clock pulse is used for reference.

Note 3: C_L = 15 pF, R_L = 280Ω, T_A = 25°C and V_{CC} = 5V.

Note 4: C_L = 50 pF, R_L = 280Ω, T_A = 25°C and V_{CC} = 5V.

Note 5: Data includes the two serial inputs and the eight input/output data lines.

Note 6: T_A = 25°C and V_{CC} = 5V.

Electrical Characteristics

over recommended operating free air temperature (unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ (Note 6) | Max | Units |
|-----------------|-----------------------------------|--|-----|-----------------|-------|-------|
| V _I | Input Clamp Voltage | V _{CC} = Min, I _I = -18 mA | | | -1.2 | V |
| V _{OH} | High Level Output Voltage | V _{CC} = Min, I _{OH} = Max Q _A thru Q _H | 2.4 | 3.2 | | V |
| | | V _{IL} = Max, V _{IH} = Min Q _A , Q _H | 2.7 | 3.4 | | |
| V _{OL} | Low Level Output Voltage | V _{CC} = Min, I _{OL} = Max V _{IH} = Min, V _{IL} = Max | | | 0.5 | V |
| I _I | Input Current @ Max Input Voltage | V _{CC} = Max, V _I = 5.5V | | | 1 | mA |
| I _{IH} | High Level Input Current | V _{CC} = Max V _I = 2.7V | | | 100 | μA |
| | | A thru H, S0, S1 | | | 50 | |
| I _{IL} | Low Level Input Current | V _{CC} = Max V _I = 0.5V | | | -2 | mA |
| | | Clock, Clear | | | -0.5 | |
| | | S0, S1 | | | -0.25 | |
| | | Other | | | -0.25 | |

Electrical Characteristics (Continued)

over recommended operating free air temperature (unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ (Note 6) | Max | Units |
|-----------|--|---|-----|-----------------|------|---------|
| I_{OZH} | Off-State Output Current with High Level Output Voltage Applied (Q_A thru Q_H) | $V_{CC} = \text{Max}$, $V_O = 2.4V$ $V_{IH} = \text{Min}$, $V_{IL} = \text{Max}$ | | | 100 | μA |
| I_{OZL} | Off-State Output Current with Low Level Output Voltage Applied (Q_A thru Q_H) | $V_{CC} = \text{Max}$, $V_O = 0.5V$ $V_{IH} = \text{Min}$, $V_{IL} = \text{Max}$ | | | -250 | μA |
| I_{OS} | Short Circuit Output Current (Q_A thru Q_H) | $V_{CC} = \text{Max}$ (Note 8) | -40 | | -100 | mA |
| | Short Circuit Output Current (Q_A , Q_H) | $V_{CC} = \text{Max}$ (Note 8) | -20 | | -100 | |
| I_{CC} | Supply Current | $V_{CC} = \text{Max}$ | | 140 | 225 | mA |

Note 7: All typicals are at $V_{CC} = 5V$, $T_A = 25^\circ C$.

Note 8: Not more than one output should be shorted at a time, and the duration should not exceed one second.

Switching Characteristics

at $V_{CC} = 5V$ and $T_A = 25^\circ C$ (See Section 1 for Test Waveforms and Output Load)

| Symbol | Parameter | From (Input) To (Output) | $R_L = 280\Omega$ (Note 10) | | | | Units |
|-----------|--|---|-----------------------------|-----|----------------------|-----|-------|
| | | | $C_L = 15\text{ pF}$ | | $C_L = 50\text{ pF}$ | | |
| | | | Min | Max | Min | Max | |
| f_{MAX} | Maximum Clock Frequency | (Note 11) | 50 | | 40 | | MHz |
| t_{PLH} | Propagation Delay Time Low to High Level Output (Note 10) | Clock to Q_A or Q_H | | 20 | | 22 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output (Note 10) | Clock to Q_A or Q_H | | 20 | | 23 | ns |
| t_{PLH} | Propagation Delay Time Low to High Level Output | Clock to Q_A thru Q_H | | | | 21 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output | Clock to Q_A thru Q_H | | | | 21 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output (Note 10) | Clear to Q_A or Q_H | | 21 | | 24 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output | Clear to Q_A thru Q_H | | | | 24 | ns |
| t_{PZH} | Output Enable Time to High Level Output | $\overline{G}1, \overline{G}2$ to Q_A thru Q_H | | | | 18 | ns |
| t_{PZL} | Output Enable Time to Low Level Output | $\overline{G}1, \overline{G}2$ to Q_A thru Q_H | | | | 18 | ns |
| t_{PHZ} | Output Disable Time to High Level Output (Note 9) | $\overline{G}1, \overline{G}2$ to Q_A thru Q_H | | 12 | | | ns |
| t_{PLZ} | Output Disable Time to Low Level Output (Note 9) | $\overline{G}1, \overline{G}2$ to Q_A thru Q_H | | 12 | | | ns |

Note 9: $C_L = 5\text{ pF}$.

Note 10: $R_L = 1K\Omega$ for delays measured to Q_A and Q_H .

Note 11: For testing f_{MAX} all outputs are loaded simultaneously.

Function Table

| Mode | Inputs | | | | | | Inputs/Outputs | | | | | | | | Outputs | | | |
|-------------|--------|-----------------|----|-------------------------|-------------------------|-------|----------------|----|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| | Clear | Function Select | | Output Control | | Clock | Serial | | A/Q _A | B/Q _B | C/Q _C | D/Q _D | E/Q _E | F/Q _F | G/Q _G | H/Q _H | Q _A ' | Q _H ' |
| | | S1 | S0 | $\overline{G1}^\dagger$ | $\overline{G2}^\dagger$ | | SL | SR | | | | | | | | | | |
| Clear | L | X | L | L | L | X | X | X | L | L | L | L | L | L | L | L | L | L |
| | L | L | X | L | L | X | X | X | L | L | L | L | L | L | L | L | L | L |
| Hold | H | L | L | L | L | X | X | X | Q _{A0} | Q _{B0} | Q _{C0} | Q _{D0} | Q _{E0} | Q _{F0} | Q _{G0} | Q _{H0} | Q _{A0} | Q _{H0} |
| | H | X | X | L | L | L | X | X | Q _{A0} | Q _{B0} | Q _{C0} | Q _{D0} | Q _{E0} | Q _{F0} | Q _{G0} | Q _{H0} | Q _{A0} | Q _{H0} |
| Shift Right | H | L | H | L | L | ↑ | X | H | H | Q _{An} | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | H | Q _{Gn} |
| | H | L | H | L | L | ↑ | X | L | L | Q _{An} | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | L | Q _{Gn} |
| Shift Left | H | H | L | L | L | ↑ | H | X | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | Q _{Hn} | H | Q _{Bn} | H |
| | H | H | L | L | L | ↑ | L | X | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | Q _{Hn} | L | Q _{Bn} | L |
| Load | H | H | H | X | X | ↑ | X | X | a | b | c | d | e | f | g | h | a | h |

†When one or both output controls are high the eight input/output terminals are disabled to the high-impedance state; however, sequential operation or clearing of the register is not affected


a...h = the level of the steady-state input at inputs A through H, respectively. These data are loaded into the flip-flops while the flip-flop outputs are isolated from the input/output terminals.

Q_{A0}...Q_{H0} = The output logic level of Q_x before the indicated input conditions were established.


H = high level, L = low logic level, X = either low or high logic level

Q_{An}...Q_{Hn} = The output logic level before the active transition (↑) of the clock input.

Logic Diagram



Physical Dimensions inches (millimeters) unless otherwise noted



20-Lead Molded Dual-In-Line Package (N)
Order Number DM74S299N
Package Number N20A

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Fairchild Semiconductor Corporation
 Americas
 Customer Response Center
 Tel: 1-888-522-5372

Fairchild Semiconductor Europe
 Fax: +49 (0) 1 80-530 85 86
 Email: europe.support@nsc.com
 Deutsch Tel: +49 (0) 8 141-35-0
 English Tel: +44 (0) 1 793-85-68-56
 Italy Tel: +39 (0) 2 57 5631

Fairchild Semiconductor Hong Kong Ltd.
 13th Floor, Straight Block,
 Ocean Centre, 5 Canton Rd.
 Tsimshatsui, Kowloon
 Hong Kong
 Tel: +852 2737-7200
 Fax: +852 2314-0061

National Semiconductor Japan Ltd.
 Tel: 81-3-5620-6175
 Fax: 81-3-5620-6179

www.fairchildsemi.com