



## Features

- 3 kA, 8/20  $\mu$ s surge capability
- Low clamping voltage under surge
- Bidirectional TVS
- UL Recognized 



The PTVS3-xxxC Series is currently available, but not recommended for new designs. The PTVSx-xxxC-TH Series is recommended.

## Applications

- AC line protection
- High power DC bus protection

# PTVS3-xxxC Series High Current TVS Diodes

### General Information

The PTVS3-xxxC range of high current bidirectional TVS diodes is designed for use in AC line protection and high power DC bus clamping applications. These devices offer bidirectional port protection from 58 volts to 430 volts.

The devices are RoHS\* and UL compliant while also meeting IEC 61000-4-5 8/20  $\mu$ s current surge requirements.



### Agency Approval

Description	
UL	File Number: E313168

### Absolute Maximum Ratings (@ $T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

Rating	Symbol	Value	Unit
Repetitive Standoff Voltage	$V_{WM}$	58	V
		66	
		76	
		380	
		430	
Peak Current Rating per 8/20 $\mu$ s IEC 61000-4-5	$I_{PPM}$	3	kA
Operating Junction Temperature Range	$T_J$	-55 to +150	$^\circ\text{C}$
Storage Temperature Range	$T_S$	-55 to +150	$^\circ\text{C}$
Lead Temperature, Soldering (10 s)		260	$^\circ\text{C}$

### Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$I_D$ Standby Current	$V_D = V_{WM}$			10	$\mu\text{A}$	
$V_{(BR)}$ Breakdown Voltage	$I_{BR} = 10\text{ mA}$	PTVS3-058C	64	66	70	V
		PTVS3-066C	72	77	82	
		PTVS3-076C	85	92	95	
		PTVS3-380C	401	420	443	
		PTVS3-430C	440	470	490	
$V_C$ Clamping Voltage	$I_{PP} = 3\text{ kA}$	PTVS3-058C		85	100	V
		PTVS3-066C		100	120	
		PTVS3-076C		110	130	
		PTVS3-380C		510	570	
		PTVS3-430C		560	620	
$V_{(BR)}$ Temperature Coefficient			0.1		$\%/^\circ\text{C}$	
C Capacitance	F = 10 kHz, $V_d = 1\text{ Vrms}$	PTVS3-058C		2.0	2.3	nF
		PTVS3-066C		1.7	2.2	
		PTVS3-076C		1.5	2.0	
		PTVS3-380C		0.7	1.2	
		PTVS3-430C		0.6	1.0	

\*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.


The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# PTVS3-xxxC Series High Current TVS Diodes

**BOURNS®**

## Product Dimensions

The product is epoxy encapsulated per UL Class 94V-0 with Ag plated leads solderable per MIL-STD-750, Method 2026. The package dimensions and part marking are shown below.



Dim.	PTVS3-058C	PTVS3-066C	PTVS3-076C	PTVS3-380C	PTVS3-430C
A	$\frac{24.15 \pm 0.72}{(0.950 \pm 0.028)}$				
B	$\frac{2.40}{(0.094)}$ Typ.				
C	$\frac{15.0}{(0.59)}$ Min.				
D	$\frac{10.5}{(0.413)}$ Max.				
E	$\frac{1.25 \pm 0.05}{(0.049 \pm 0.002)}$				
F	$\frac{10.5}{(0.413)}$ Max.				
G	$\frac{5.0}{(0.20)}$ Max.	$\frac{5.0}{(0.20)}$ Max.	$\frac{6.0}{(0.24)}$ Max.	$\frac{17.0}{(0.67)}$ Max.	$\frac{17.0}{(0.67)}$ Max.
H	$\frac{6.60}{(0.26)}$ Max.				


DIMENSIONS:  $\frac{\text{MM}}{(\text{INCHES})}$

## Typical Part Marking


PTVS3-058C .....	3058
PTVS3-066C .....	3066
PTVS3-076C .....	3076
PTVS3-380C .....	3380
PTVS3-430C .....	3430

## Application

A typical application for Power TVS products includes AC power line primary protection.



## How to Order




Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# PTVS3-xxxC Series High Current TVS Diodes




## Performance Graphs


### V-I Characteristic



### Typical $V_{BR}$ vs. Junction Temperature



### Typical Peak Power Derating




Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# PTVS3-xxxC Series High Current TVS Diodes




## Performance Graphs (Continued)


### Surge Response (1.2/50, 8/20 Surge) - PTVS3-058C




### Surge Response (1.2/50, 8/20 Surge) - PTVS3-076C




### Surge Response - PTVS3-380C




### Surge Response (1.2/50, 8/20 Surge) - PTVS3-380C



### Surge Response - PTVS3-430C



### Surge Response (1.2/50, 8/20 Surge) - PTVS3-430C



REV. 01/14

Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.