


Central
Semiconductor Corp.
Central
Semiconductor Corp.
Central
Semiconductor Corp.
Central™
Semiconductor Corp.
145 Adams Avenue
Hauppauge, New York 11788



2N3726

2N3727

PNP DUAL SILICON TRANSISTOR

JEDEC TO-78 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N3726, 2N3727 types are silicon PNP dual transistors manufactured by the epitaxial planar process utilizing 2 individual chips mounted in a hermetically sealed metal case designed for differential amplifier applications.

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL		UNIT
Collector-Base Voltage	V_{CB0}	45	V
Collector-Emitter Voltage	V_{CE0}	45	V
Emitter-Base Voltage	V_{EB0}	5.0	V
Collector Current	I_C	300	mA
Base Current	I_B	100	mA
Power Dissipation (One Die)	P_D	400	mW
Power Dissipation (Both Dice)	P_D	500	mW
Power Dissipation (One Die, $T_C=25^\circ\text{C}$)	P_D	850	mW
Power Dissipation (Both Dice, $T_C=25^\circ\text{C}$)	P_D	1400	mW
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 to +200	$^\circ\text{C}$
Collector 1 to Collector 2 Voltage (Voltage Rated From Any Lead to the Case)	V_{C1}, V_{C2}	± 200	V

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I_{CB0}	$V_{CB}=30\text{V}$		10	nA
I_{CB0}	$V_{CB}=30\text{V}, T_A=150^\circ\text{C}$		10	μA
I_{EB0}	$V_{BE}=3.0\text{V}$		0.1	μA
BV_{CB0}	$I_C=10\mu\text{A}$	45		V
BV_{CE0}	$I_C=10\text{mA}$	45		V
BV_{EB0}	$I_E=10\mu\text{A}$	5.0		V
$V_{CE(SAT)}$	$I_C=50\text{mA}, I_B=2.5\text{mA}$		0.25	V
$V_{BE(SAT)}$	$I_C=50\text{mA}, I_B=2.5\text{mA}$		1.0	V
h_{FE}	$V_{CE}=5.0\text{V}, I_C=10\mu\text{A}$	80	-	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=100\mu\text{A}$	120	-	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=1.0\text{mA}$	135	350	
h_{FE}	$V_{CE}=5.0\text{V}, I_C=50\text{mA}$	115	-	
h_{fe}	$V_{CE}=10\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	135	420	
f_T	$V_{CE}=10\text{V}, I_C=1.0\text{mA}, f=20\text{MHz}$	60	-	MHz
f_T	$V_{CE}=20\text{V}, I_C=50\text{mA}, f=100\text{MHz}$	200	600	MHz
h_{ie}	$V_{CE}=10\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	-	11.5	$k\Omega$
h_{re}	$V_{CE}=10\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$	-	1500	$\times 10^{-6}$
h_{oe}	$V_{CE}=10\text{V}, I_C=1.0\text{mA}, f=1.0\text{kHz}$		80	μmhos
C_{ib}	$V_{EB}=0.5\text{V}, I_C=0, f=1.0\text{MHz}$		30	pF
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1.0\text{MHz}$		8.0	pF
NF	$V_{CE}=5.0\text{V}, I_C=30\mu\text{A}, R_S=10k\Omega, f=1.0\text{kHz}, BW=200\text{Hz}$		4.0	dB

(ELECTRICAL CHARACTERISTICS CONTINUED ON OTHER SIDE)

MATCHING CHARACTERISTICS:

		<u>MIN</u>	<u>MAX</u>
$ V_{BE1}-V_{BE2} $	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA$ (2N3726)		5.0
$ V_{BE1}-V_{BE2} $	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA$ (2N3727)		2.5
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA, T_A=-55^\circ C \text{ to } +25^\circ C$ (2N3726)		1.6
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA, T_A=-55^\circ C \text{ to } +25^\circ C$ (2N3727)		0.8
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA, T_A=+25^\circ C \text{ to } +125^\circ C$ (2N3726)		2.0
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}=5.0V, I_C=0.1mA \text{ to } 1.0mA, T_A=+25^\circ C \text{ to } +125^\circ C$ (2N3727)		1.0
h_{FE1}/h_{FE2}	$V_{CE}=5.0V, I_C=0.1 \text{ to } 1.0mA$	0.9	1.0

Central[™]
Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824
www.centrasemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centalsemi.com

Worldwide Field Representatives:
www.centalsemi.com/wwreps

Worldwide Distributors:
www.centalsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centalsemi.com/terms



http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

Summary: All transistors manufactured in the TO-78 package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

<u>Central Part Number</u>	<u>Replacement</u>
CEN876	N/A
CEN894	N/A
CEN895	N/A
CEN896	N/A
CEN911	N/A
CEN947	N/A
CEN955 W/DATA	N/A
MD2219A	N/A
MD2369	N/A
MD2369A	N/A
MD2369B	N/A
MD2905	N/A
MD2905A	N/A
MD5179	N/A
MD7000	N/A
MD7001	N/A
MD7003	N/A
MD7003A	N/A
MD7003B	N/A
MD8002	N/A
MD8003	N/A
MD918	N/A
MD918A	N/A
MD918B	N/A
MD984	N/A
2N2060	N/A
2N2060A	N/A
2N2060M	N/A
2N2223	N/A
2N2223A	N/A
2N2453	N/A
2N2453A	N/A
2N2480	N/A
2N2480A	N/A
2N2639	N/A
2N2640	N/A
2N2641	N/A
2N2642	N/A

*** CONTINUED ***

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

<u>Central Part Number</u>	<u>Replacement</u>
2N2643	N/A
2N2644	N/A
2N2652	N/A
2N2652A	N/A
2N2720	N/A
2N2721	N/A
2N2722	N/A
2N2903	N/A
2N2903A	N/A
2N2913	N/A
2N2914	N/A
2N2915	N/A
2N2915A	N/A
2N2916	N/A
2N2916A	N/A
2N2917	N/A
2N2918	N/A
2N2919	N/A
2N2919A	N/A
2N2920	N/A
2N2920A	N/A
2N3726	N/A
2N3727	N/A
2N3806	N/A
2N3807	N/A
2N3808	N/A
2N3809	N/A
2N3810	N/A
2N3810A	N/A
2N3811	N/A
2N3811A	N/A
2N4015	N/A
2N4016	N/A
2N4854	N/A
2N4937	N/A
2N4938	N/A
2N4939	N/A
2N5793	N/A
2N5794	N/A
2N5796	N/A
2N5912	N/A
2N6502	N/A

*** CONTINUED ***

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



<http://www.centrasemi.com>

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

Central Part Number _____ **Replacement** _____

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centrasemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.