



POS.	A -0.76	B -0.25	C	PART NO.
9	31.19	16.46	25.00 ^{+0.12} _{-0.13}	242A15030X
15	39.52	24.79	33.30 ^{+0.15} _{-0.1}	242A15040X
25	53.42	38.50	47.04 ^{+0.13}	242A15050X
37	69.70	54.96	63.50 ^{+0.13}	242A15060X

NOTES:

- METALSHELLS: STEEL; TIN PLATED
- INSULATOR: PBTP GF UL 94 V-0
- CONTACTS: COPPER ALLOY
- PLATING: HARD GOLD OVER NICKEL
- PCB-SNAP: COPPER ALLOY; TIN PLATED
PCB HOLE ϕ 3.1±0.1; PCB THICKNESS $t=1.6$ mm
- CAPACITANCE: 1300pF±20%
- DIELECTRIC WITHSTANDING VOLTAGE: 424VDC
- MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
- = CRITICAL DIMENSION: SPC

used for: D-SUB FILTER

DO NOT ALTER CAD DRAWING BY HAND
OWNERSHIP AND COPYRIGHT OF CONEC GMBH
WRITTEN PERMISSION
BE PASSED ON TO A THIRD PARTY WITHOUT
REPRODUCED IN ANY WAY, AND MAY NOT
THIS DRAWING MAY NOT BE COPIED OR

CONEC CORPORATION BRAMPTON, ONTARIO		tolerance	2:1 (5:1)
		material:	SEE NOTES
		title:	D-FILTER FEMALE P-TYP 9-37pos. PIN 5.8mm WITH THREADED SPACER CLIP
1996	date	name	DIN-A
drawn	08.05.	Barcinski	3
appd.	08.05.	Mickenbecker	sh: 1/1
norm	DIN 41652		
d-old			

rev. description date name

dwg no: 24K11Y8A

product no: SEE TABLE

CONEC