

Diagonal Cutters

DIN ISO 5749

70

- > the essential cutting tool for all-around use
- > high-quality material and precise workmanship for long service life
- > precision cutting edges for soft and hard wire
- > clean cutting of thin copper wires, even at the cutting edge tips
- > induction hardened cutting edges (approx. 62 HRC)
- > narrow head style for use in confined areas
- > vanadium steel; forged, multi stage oil-hardened



Clean cutting of thin copper wires, also at the cutting edge tips



70 01 180



70 02 180



70 08 180 SBA



⚡ 1000 V ASTM



70 11 110



Product Number	Packaging	↔ Inch mm		Pliers	Head	Handles	Cutting capacities			⚖ lbs
							⊘ Inch Ø mm	⊘ Inch Ø mm	⊘ Inch Ø mm	
70 01 110		4 1/4 110					1/8 3.0	5/64 2.0	3/64 1.2	0.18
70 01 125		5 125	✓	black atramentized	polished	3 plastic coated	1/8 3.0	3/32 2.3	1/16 1.5	0.18
70 01 140		5 1/2 140	✓				5/32 4.0	3/32 2.5	5/64 1.8	0.28
70 01 180		7 1/4 180					5/32 4.0	1/8 3.0	3/32 2.5	0.44
70 02 125		5 125					1/8 3.0	3/32 2.3	1/16 1.5	0.26
70 02 140		5 1/2 140	✓	black atramentized	polished	multi-component grips	5/32 4.0	3/32 2.5	5/64 1.8	0.35
70 02 180		7 1/4 180					5/32 4.0	1/8 3.0	3/32 2.5	0.57
70 08 180 SBA	X	7 1/4 180	⚡	1000 V ASTM	polished	insulated, multi-component handles, ASTM-tested	5/32 4.0	1/8 3.0	3/32 2.5	0.58
70 11 110		4 1/4 110	✓	black atramentized	polished	plastic coated	1/8 3.0	5/64 2.0	3/64 1.2	0.20