



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 56.13 mm, Rated current: 309 A; Colour: Yellow

RAL: 1026

Business data

Article number	2767.2
Article name	AQI 2/150 YE
GTIN (EAN)	4044211054977
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	156.8 g
Weight per piece (including packaging)	156.9 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2767.2
Product description	External insulated cross-connector

Technical data

Dimensions

Width	56.13 mm
-------	----------

Pitch size	31 mm
------------	-------

Ratings

Voltage with partition, max.	1000 V
------------------------------	--------

Voltage without partition, max.	1000 V
---------------------------------	--------

Rated current	309 A
---------------	-------

Contamination degree	3
----------------------	---

Connection data

No. of poles	2
--------------	---

Materials

Material	Copper
----------	--------

Surface	Tin-plated
---------	------------

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Further technical data

Mounting type	Plug in
---------------	---------

Insulation available	✓
----------------------	---

Touch protection is available	✓
-------------------------------	---

Number of bridged terminals	2
-----------------------------	---

Environmental Product Compliance

REACH Conform	Yes
---------------	-----

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	Yes
--------------	-----

Media

Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal to mounting surface, Screw connection, Mounting type: Mounting surface, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1584.2	RK 150-D BG	4044211047740	5



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1477.2	RK 150 Ex BG	4044211107864	5



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1124.2	RK 150 BG	4044211019198	5