



JKL PART NUMBER	LENGTH A +/- 1.5mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (Cd/m <sup>2</sup> )	*RATED LIFE (HRS)
BF20218-24B	218mm	RGB HIGH OUTPUT WHITE 8400°k x = .290 y = .305	1250 @ 0°C	500	5 ± 1	46,000 TYP.	40,000
BF20226-24B	226mm		1275 @ 0°C	510			
BF20292-24B	292mm		1650 @ 0°C	660			
BF20325-24B	325mm		1830 @ 0°C	735			

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>							
			TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>									
<b>B</b> RATED LIFE HRS TO 40,000 <b>A</b> RATING ADDITIONS & CHANGES RELEASED TO CAD MULTI LIST			DRAWN BY L. WENGSTROM		APPVD BY DATE J.V. 8/25/10		SIZE <b>A</b>		FSCM NO. <b>55335</b>		DRAWING NO. <b>BF 20-24B</b>	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>		RELEASED DATE 8/14/03		REVISION DATE 8/25/10		REV. NO. <b>B</b> SHEET 1 OF 1	