



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

70 MHz LC Band Pass Filter

Part Number: AE70B5476



Electrical Specifications

Center Frequency: 70 MHz
3 dB Bandwidth: 30 MHz Min.
Insertion Loss: 3.0 dB Max.
Return Loss: 14.0 dB Min.
Rejection1: 65 dB Min @ 28 MHz
Rejection2: 65 dB Min @ 112 MHz


Mechanical

Connector Type: PC-Mount
Dimensions: 1.5" X 0.38" x 0.38".

Environmental

Operating Temperature: -25°C to +70°C
Storage Temperature: -40°C to +90°C
Shock: 10 G. 11ms
Vibration: 10 G. 5 to 200Hz

Outline Drawing:



Tolerance: +/-0.01 inches [+/-0.3mm]

Angles: +/-1 Deg.

*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.


*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 321-3941

Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com



Simulation Plot:



Note: This is a simulated response plot. Actual performance might differ.