

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

<b>APPLICABLE STANDARD</b>					
OPERATING TEMPERATURE RANGE		-35°C TO 85°C (NOTE 1)		STORAGE TEMPERATURE RANGE	
RATING				-10°C TO 60°C	
VOLTAGE		30V AC/DC		APPLICABLE CONNECTOR	
CURRENT		0.3A		BM20* (0.8) -20DP-0.4V (**)	
<b>SPECIFICATIONS</b>					
ITEM	TEST METHOD		REQUIREMENTS		Q/T A/T
<b>CONSTRUCTION</b>					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		CONFIRMED VISUALLY.		X X
MARKING					X X
<b>ELECTRIC CHARACTERISTICS</b>					
CONTACT RESISTANCE	20mV AC OR LESS 1kHz, 1m A.		100mΩ MAX.		X -
INSULATION RESISTANCE	100V DC.		50MΩ MIN.		X -
VOLTAGE PROOF	100V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X -
<b>MECHANICAL CHARACTERISTICS</b>					
MECHANICAL OPERATION	10TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X -
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 100CYCLES, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X -
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X -
<b>ENVIRONMENTAL CHARACTERISTICS</b>					
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +85°C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2-3 min)		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X -
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X -
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)		① CONTACT RESISTANCE: 100mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.		X -
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED
DATE					
REMARKS					
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402 AND IEC 60512.					
Note Q.T:Qualification Test A.T:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-332315-01	
<b>HRS</b>		SPECIFICATION SHEET		PART NO. BM20B (0.8) -20DS-0.4V (51)	
HIROSE ELECTRIC CO., LTD.		CODE NO. CL684-9009-7-51		1/1	