

MATE-N-LOK | Micro MATE-N-LOK

TE Internal #: 2-794615-0

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 20 Position, 3 mm [.118 in] Centerline, Wire & Cable,

Micro MATE-N-LOK

View on TE.com >




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 20

Centerline (Pitch): 3 mm [.118 in]

Features

Product Type Features

Product Type Features	
Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	20
Number of Rows	2
Electrical Characteristics	
Operating Voltage	250 VDC
Contact Features	
Contact Retention Within Housing	Without

Pin

Contact Type



Termination Features

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
Panel Mount Feature	With
Panel Mount Feature Type	Locking Latch
Mating Retention Type	Locking Tab
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	3 mm[.118 in]
Housing Color	Black
Housing Material	Nylon
Dimensions	
Panel Thickness (Recommended)	1.57 – 2.3 mm[.062 – .091 in]
	1.57 – 2.3 mm[.062 – .091 in] 1.52 mm[.06 in]
Panel Thickness (Recommended)	
Panel Thickness (Recommended) Compatible Insulation Diameter (Max)	1.52 mm[.06 in]
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height	1.52 mm[.06 in] 8.71 mm
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length	1.52 mm[.06 in] 8.71 mm 30.85 mm
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing	1.52 mm[.06 in] 8.71 mm 30.85 mm
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in]
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in]
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F]
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Circuit Application	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F]
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F] Power & Signal
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F] Power & Signal UL 94V-0
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating Glow Wire Rating	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F] Power & Signal UL 94V-0
Panel Thickness (Recommended) Compatible Insulation Diameter (Max) Connector Height Product Length Row-to-Row Spacing Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating Glow Wire Rating Packaging Features	1.52 mm[.06 in] 8.71 mm 30.85 mm 3 mm[.118 in] -40 – 105 °C[-40 – 221 °F] Power & Signal UL 94V-0 Standard Part - Not Glow Wire



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Micro MATE-N-LOK





Insertion & Extraction Tools(1)



Power Contacts(27)



Rectangular Power Connectors(479)

Customers Also Bought



TE Part #1-794617-8 18POS,MICRO MNL,RCPT HSG



TE Part #2-794617-0 20POS,MICRO MNL,RCPT HSG



TE Part #794615-4
PANEL MT DBL ROW HSG 4 POS



TE Part #1-794609-1 PIN CONT 26-30 15 GOLD STRIP




TE Part #1-794612-1 PIN CONT 20-24 15 GOLD L/P



TE Part #1-794615-2
PANEL MT DBL ROW HSG 12 POS



TE Part #1-794615-4
PANEL MT DBL ROW HSG 14 POS



TE Part #1-794615-8
PANEL MT DBL ROW HSG 18 POS



TE Part #794615-8
PANEL MT DBL ROW HSG 8 POS



Documents

Product Drawings

PANEL MT DBL ROW HSG 20 POS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-794615-0_C1.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_2-794615-0_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-794615-0_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English