## 0.5 METER LENGTH



Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 172180 N-Type Plug Right Angle Brass White Bronze + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle	Connector A			Cable			Connector B		
30° 135° 225° 270° 270° D-Flat Bulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	112234 BNC Clamp BHD JK RG188 500 BNC Jack Straight Crimp Standard 50 Ohm Bulkhead - Rear Mount Brass Nickel None Beryllium Copper Silver 4 GHz BNC Jack Straight BHD		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 0.5 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	172180 N-Type R/A PLUG RG174 RG316 LMR100 500 N-Type Plug Right Angle Solder Standard 50 Ohm Cable Brass White Bronze None Brass Gold 11 GHz N-Type Plug Right Angle 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT CONTROLLED DOCUMENT DO NOT CODY			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT. ESTABLISHES AND AGREEME	AND MUST NOT BE U ITAL TO CUSTOM CA JCED OR TRANSCRIB WRITTEN CONSENT C ANCE OF THIS DRAW	BLE ED F ING Part No:	BNC-ST-JK/N-RA-PL G174 0.5M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	