

CAT5 UTP 180° KEYSTONE JACK 110 STYLE, TOOLLESS, W/6 COLOR ID,
568B WIRING LABEL, ANSI/TIA 568.2-D, ISO/IEC 11801 CLASS D, UL - 1 EA/BAG

SCP PART#:
S45-3500B
S45-3500W

PRODUCT SUMMARY

For Networks Using Cat5E UTP Cabling
Toolless Design for Fast and Easy Terminations,
ANSI/TIA 568.2-D; ISO/IEC 11801 Class D
PoE IEEE 802.3bt

KEY FEATURES

- Interchangeable (6) Color Coded Snap-On Bars
- Narrow Design Supports Side-by-Side Installation in Patch Panels
- Wire Layout Diagram Simplifies Termination and Reduces Untwisting of Cable Wires
- Supports Cat5e UTP Cabling
- Toolless Design Requires No Punchdown or Specialty Tooling
- 180° Degree Design is Ideal for Patch Panel Applications
- UL Listed
- Professional Quality

PRODUCT DIMENSIONS

SIZE: 1.4" L x 0.8" H x 0.6" W
36.74mm L x 21.64mm H x 17.01 mm W

SPECIFICATIONS

Standards:
ISO/IEC 11801 Class D
ANSI/TIA 568.2-D
ANSI/TIA 1096-A
ANSI/TIA 606-C
EN 50173
IEC 60603-7-51
PoE/PoH: IEEE 802.3bt
UL 1863, cULus Listed

Electrical:
Insulation Resistance: $\geq 500 \text{ M}\Omega$
Dielectric Withstand Volt: 100VAC
RMS 60Hz
Contact Resistance: $\leq 20 \text{ m}\Omega$
Current Rating: 1.5A at 68F

Mechanical:
24AWG Wire Conductors – Cat5e UTP cabling
Plug Insertion Life: ≥ 750 times plug in
Contact Force 99.2g (3.5oz) FCC Plug
Plug Retention Force: 30lb (133n/13/3kg)
Temperature (Installation): -40F to 150F (-40C to 66C)
Temperature (Operating): -10C to 60C
Contact Plating: 50 μ 24ct gold

CONFIGURATION

Part #	Description
S45-3500W	Cat5e UTP 180° Keystone Jack 110 Style, Toolless - White
S45-3500B	Cat5e UTP 180° Keystone Jack 110 Style, Toolless - Black

