2.5 METERS LENGTH






Connector A 132246 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 172177 N-Type Plug Right Angle Brass White Bronze + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



333				4	
132246	Part #:	RG-58	Part #:	172177	
SMA R/A BHD JK RG58 LMR195 500	Description:	RG-58 - PE 0.196	Description:	N-Type R/A PLUG RG58 LMR195 50O	
SMA	Dielectric:	PE	Type:	N-Type	
Jack	Shielding:	Braid	Gender:	Plug	
Right Angle	Diameter:	0.196	Body Type:	Right Angle	
Solder	Impedance:	50 Ohm	Contact Type:	Solder	
Standard	Sheathing:	None	Polarity:	Standard	
50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Bulkhead - Rear Mount	Length:	2.5 Meters	Mounting:	Cable	
Brass			Body Material:	Brass	
Gold			Body Finish:	White Bronze	
None			IP Rating:	None	
Beryllium Copper			Contact Material:	Brass	
Gold			Contact Finish:	Gold	
12.4 GHz			Max. Freq.:	11 GHz	
Booting: SMA Jack Right Angle			Booting:	N-Type Plug Right Angle	
			Clocking:	0°	
	SMA R/A BHD JK RG58 LMR195 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz	SMA R/A BHD JK RG58 LMR195 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	SMA R/A BHD JK RG58 LMR195 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz Diescription: RG-58 - PE 0.196 Dielectric: PE Shielding: Braid Diameter: 0.196 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: 2.5 Meters	SMA R/A BHD JK RG58 LMR195 500 SMA Jack Right Angle Solder Standard Solohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right Angle Description: RG-58 - PE 0.196 Description: PE Type: Gender: Braid Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Brass Gold Length: J.5 Meters Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/N-RA-PL RG58 2.5M

Part No

Q-2R02F00082.5M

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-2R02F00082.5M

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-JK/N-RA-PL RG58 2.5M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

