

1

2

3


4

5


6

7

A



RECOMMENDER PCB LAYOUT



Material

- | | |
|---------------------|-------------------------------|
| ① Insulating body: | Thermoplastic (UL94V-0), GREY |
| ② Insulating cover: | Thermoplastic (UL94V-0), GREY |
| ③ Insulating lever: | Thermoplastic (UL94V-0), GREY |
| ④ Contact pin: | Brass, Tin plated |
| ⑤ Spring clamp: | Stainless steel |

Electrical cULus

Voltage rating: 300V
 Current rating: 6A
 Wire range:
 Solid wire(AWG): 16-26
 Stranded wire(AWG): 16-26
 Wire strip length: 6-7mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval:

B

A

B

C

C

D



D

E

E

F

F



DIMENSION

L	Nx5.0+1.00
P	(N-1)x5.0


N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-4p	±0.15	±0.15
5p-9p	±0.20	±0.20
10p-14p	±0.30	±0.30
15p-19p	±0.40	±0.40
20p-24p	±0.50	±0.50

G

G

RoHS compliant
Unit: mm



Scale	1:1	Date	19.04.2010	Name	Alex	Customer-No.	
TOLERANCE		Drawn	19.04.2010	Alex		ASSMANN WSW-No. A-TB500-HXxxV	
X.	±0.50	Approved	19.04.2016	Joanna			
X.X	±0.30					Drawing-No.	
X.XX	±0.10					ASS 4124 CO	rev01
DIM	TOL	① Add UL	19.04.2016	Joanna		Replace	Sheet
X.°	±1°	① Drawn	19.04.2010	Alex			
Angle	TOL	Id.	Modification	Date		Name	

H

H

1

2

3

4

5

6

7