

Specification Sheet

Part Number: 133-00998



Separates and secures bundles avoiding abrasion.

Designed to handle both convoluted tubing and bundles not covered in convoluted tubing.

Available in a variety of sizes and colors to be easily identified.

Article Number 133-00998

Type HC3A

Color Black (BK)

Quantity Per bag

Product Description HC Clamps separate multiple bundles and secure them to brackets or frame rails. Each mount has two pawls for easy pre-installation on a threaded fastener prior to securing with a mechanical fastener. HC Clamps have ribs that make them ideal for convoluted tubing, but they can also be used to separate separate bundles that aren't protected with convoluted tubing.

Short Description HC Clamp Bundle Separator, Three Hole, PA66GFHIRHS, Black, 500/pkg

Global Part Name HC3A-PA66HIRGF13-BK

Length L (Imperial) 4.246

Length L (Metric) 107.86

Variant Separators

Width W (Imperial) 1.1

Width W (Metric) 27.94

Bundle Diameter Min (Imperial) 0.96

Bundle Diameter Min (Metric) 24.39

Bundle Diameter Max (Imperial) 0.9

Bundle Diameter Max (Metric) 24.3

Bundle Diameter 1st Loop Max (Imperial) 0.96

Bundle Diameter 1st Loop Max (Metric) 24.39

Bundle Diameter 2nd Loop Max (Imperial) 0.96

Bundle Diameter 2nd Loop Max (Metric) 24.39

Height H (Imperial) 1.38

Height H (Metric) 34.94

| | |
|---------------------------------------|---|
| Mounting Hole Diameter D (Imperial) | 0.32 |
| Mounting Hole Diameter D (Metric) | 8.12 mm |
| Mounting Hole Diameter D Max (Metric) | 8.12 |
| Material | Polyamide 6.6, high impact modified, glass-fiber reinforced (PA66HIRGF13) |
| Material Shortcut | PA66HIRGF13 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar,

electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)