

**Data sheet | Item number: 279-604**

4-conductor through terminal block; 1.5 mm<sup>2</sup>; suitable for Ex i applications; lateral marker slots; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 1,50 mm<sup>2</sup>; blue

[www.wago.com/279-604](http://www.wago.com/279-604)



**Data**

**Electrical data**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Ratings per IEC/EN

|                               |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Ratings per                   | IEC/EN 60947-7-1                                          |
| Nominal voltage (III/3)       | 800 V                                                     |
| Rated impulse voltage (III/3) | 8 kV                                                      |
| Rated current                 | 18 A                                                      |
| Legend (ratings)              | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

### Ratings per UL

|                                |         |
|--------------------------------|---------|
| Approvals per                  | UL 1059 |
| Rated voltage UL (Use Group C) | 600 V   |
| Rated current UL (Use Group C) | 10 A    |

### Ratings per CSA

|                                 |                 |
|---------------------------------|-----------------|
| Approvals per                   | CSA 22.2 No 158 |
| Rated voltage CSA (Use Group C) | 600 V           |
| Rated current CSA (Use Group C) | 10 A            |

### Power Loss

|                                                              |                |
|--------------------------------------------------------------|----------------|
| Power loss, per pole (potential)                             | 0.593 W        |
| Rated current $I_N$ for specified power loss                 | 18 A           |
| Resistance value for specified, current-dependent power loss | 0.002 $\Omega$ |

### Connection data

|                            |   |
|----------------------------|---|
| Connection points          | 4 |
| Total number of potentials | 1 |
| Number of levels           | 1 |

### Connection 1

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| Connection technology           | CAGE CLAMP®                                  |
| Actuation type                  | Operating tool                               |
| Connectable conductor materials | Copper                                       |
| Solid conductor                 | 0.08 ... 1.5 mm <sup>2</sup> / 28 ... 16 AWG |
| Fine-stranded conductor         | 0.08 ... 1.5 mm <sup>2</sup> / 28 ... 16 AWG |
| Strip length                    | 8 ... 9 mm / 0.31 ... 0.35 inches            |
| Wiring direction                | Front-entry wiring                           |

Subject to changes. Please also observe the further product documentation!



## Physical data

|                                   |                      |
|-----------------------------------|----------------------|
| Width                             | 4 mm / 0.157 inches  |
| Height                            | 68 mm / 2.677 inches |
| Depth from upper-edge of DIN-rail | 27 mm / 1.063 inches |

## Mechanical Data

|               |              |
|---------------|--------------|
| Mounting type | DIN-35 rail  |
| Marking level | Side marking |

## Material Data

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| Note (material data)        | Information on material specifications can be found here |
| Color                       | blue                                                     |
| Material group              | I                                                        |
| Insulation material         | Polyamide (PA66)                                         |
| Flammability class per UL94 | V0                                                       |
| Fire load                   | 0.18 MJ                                                  |
| Weight                      | 5.8 g                                                    |

## Environmental requirements

|                                  |                 |
|----------------------------------|-----------------|
| Processing temperature           | -35 ... +85 °C  |
| Continuous operating temperature | -60 ... +105 °C |

## Commercial data

|                       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-14-11-20   |
| eCl@ss 9.0            | 27-14-11-20   |
| ETIM 8.0              | EC000897      |
| ETIM 7.0              | EC000897      |
| PU (SPU)              | 100 pcs       |
| Packaging type        | box           |
| Country of origin     | DE            |
| GTIN                  | 4044918504287 |
| Customs tariff number | 85369010000   |

Subject to changes. Please also observe the further product documentation!



## Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

## Approvals / Certificates

### General approvals

| Logo | Approval                                     | Additional Approval Text | Certificate name |
|------|----------------------------------------------|--------------------------|------------------|
|      | <b>CCA</b><br>DEKRA Certification B.V.       | EN 60947                 | NTR NL-7081      |
|      | <b>CSA</b><br>DEKRA Certification B.V.       | C22.2 No. 158            | 70133738         |
|      | <b>KEMA/KEUR</b><br>DEKRA Certification B.V. | EN 60947                 | 2160584.04       |
|      | <b>UL</b><br>Underwriters Laboratories Inc.  | UL 1059                  | E45172           |

### Declarations of conformity and manufacturer's declarations

| Logo | Approval                                                  | Additional Approval Text | Certificate name |
|------|-----------------------------------------------------------|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |
|      | <b>UK-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

### Approvals for marine applications

| Logo | Approval                                                | Additional Approval Text | Certificate name |
|------|---------------------------------------------------------|--------------------------|------------------|
|      | <b>ABS</b><br>American Bureau of Shipping               | -                        | 20-HG1941090-PDA |
|      | <b>BV</b><br>Bureau Veritas S.A.                        | EN 60947                 | 07436/F0 BV      |
|      | <b>DNV GL</b><br>Det Norske Veritas, Germanischer Lloyd | -                        | TAE00001V2       |
|      | <b>LR</b><br>Lloyds Register                            | EN 60947                 | 91/20112 (E9)    |

## Required accessories

### End plate

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## End plate

|                                                                                                   |                                                                |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Item no.: 209-191</b><br>Separator for Ex e/Ex i applications; 3 mm thick; 120 mm wide; orange | <a href="http://www.wago.com/209-191">www.wago.com/209-191</a> |
| <b>Item no.: 279-317</b><br>End and intermediate plate; 2 mm thick; orange                        | <a href="http://www.wago.com/279-317">www.wago.com/279-317</a> |
| <b>Item no.: 279-316</b><br>End and intermediate plate; 2 mm thick; gray                          | <a href="http://www.wago.com/279-316">www.wago.com/279-316</a> |

## Optional accessories

## Tool

## Operating tool

|                                                                                                                  |                                                                |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Item no.: 210-648</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; angled; short | <a href="http://www.wago.com/210-648">www.wago.com/210-648</a> |
| <b>Item no.: 210-647</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; multicoloured | <a href="http://www.wago.com/210-647">www.wago.com/210-647</a> |
| <b>Item no.: 210-719</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft                | <a href="http://www.wago.com/210-719">www.wago.com/210-719</a> |

## Carrier rail

## Mounting accessories

|                                                                                                                                                 |                                                                |
|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Item no.: 210-197</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored                | <a href="http://www.wago.com/210-197">www.wago.com/210-197</a> |
| <b>Item no.: 210-198</b><br>Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored           | <a href="http://www.wago.com/210-198">www.wago.com/210-198</a> |
| <b>Item no.: 210-504</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored   | <a href="http://www.wago.com/210-504">www.wago.com/210-504</a> |
| <b>Item no.: 210-505</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored | <a href="http://www.wago.com/210-505">www.wago.com/210-505</a> |
| <b>Item no.: 210-506</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored  | <a href="http://www.wago.com/210-506">www.wago.com/210-506</a> |
| <b>Item no.: 210-508</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored    | <a href="http://www.wago.com/210-508">www.wago.com/210-508</a> |
| <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored             | <a href="http://www.wago.com/210-113">www.wago.com/210-113</a> |
| <b>Item no.: 210-118</b><br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored            | <a href="http://www.wago.com/210-118">www.wago.com/210-118</a> |

Subject to changes. Please also observe the further product documentation!

**Item no.: 210-112**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored

[www.wago.com/210-112](http://www.wago.com/210-112)**Item no.: 210-114**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-114](http://www.wago.com/210-114)**Item no.: 210-115**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored

[www.wago.com/210-115](http://www.wago.com/210-115)**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-196](http://www.wago.com/210-196)**End plate**

## End plate

**Item no.: 284-334**

Step-down cover plate; 1 mm thick; for 2-, 3- and 4-conductor terminal blocks; gray

[www.wago.com/284-334](http://www.wago.com/284-334)**Item no.: 284-344**

Step-down cover plate; 1 mm thick; for 2-, 3- and 4-conductor terminal blocks; orange

[www.wago.com/284-344](http://www.wago.com/284-344)**Marking accessories**

## Double marker carrier

**Item no.: 209-128**

Adaptor; gray

[www.wago.com/209-128](http://www.wago.com/209-128)

## Marker

**Item no.: 2009-114/000-002**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; yellow

[www.wago.com/2009-114/000-002](http://www.wago.com/2009-114/000-002)**Item no.: 2009-114/000-005**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; red

[www.wago.com/2009-114/000-005](http://www.wago.com/2009-114/000-005)**Item no.: 2009-114/000-007**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; gray

[www.wago.com/2009-114/000-007](http://www.wago.com/2009-114/000-007)**Item no.: 2009-114/000-023**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; green

[www.wago.com/2009-114/000-023](http://www.wago.com/2009-114/000-023)**Item no.: 2009-114/000-006**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; blue

[www.wago.com/2009-114/000-006](http://www.wago.com/2009-114/000-006)**Item no.: 2009-114/000-024**

WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; violet

[www.wago.com/2009-114/000-024](http://www.wago.com/2009-114/000-024)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



|                                                                                                                                              |                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| <b>Item no.: 2009-114/000-012</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/2009-114/000-012">www.wago.com/2009-114/000-012</a> |
| <b>Item no.: 2009-114</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; white          | <a href="http://www.wago.com/2009-114">www.wago.com/2009-114</a>                 |
| <b>Item no.: 793-4501/000-002</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; yellow                          | <a href="http://www.wago.com/793-4501/000-002">www.wago.com/793-4501/000-002</a> |
| <b>Item no.: 793-4501/000-006</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; blue                            | <a href="http://www.wago.com/793-4501/000-006">www.wago.com/793-4501/000-006</a> |
| <b>Item no.: 793-4501/000-014</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; brown                           | <a href="http://www.wago.com/793-4501/000-014">www.wago.com/793-4501/000-014</a> |
| <b>Item no.: 793-4501</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; white                                   | <a href="http://www.wago.com/793-4501">www.wago.com/793-4501</a>                 |
| <b>Item no.: 793-4501/000-023</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; green                           | <a href="http://www.wago.com/793-4501/000-023">www.wago.com/793-4501/000-023</a> |
| <b>Item no.: 793-4501/000-024</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; violet                          | <a href="http://www.wago.com/793-4501/000-024">www.wago.com/793-4501/000-024</a> |
| <b>Item no.: 793-4501/000-005</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; red                             | <a href="http://www.wago.com/793-4501/000-005">www.wago.com/793-4501/000-005</a> |
| <b>Item no.: 793-4501/000-007</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; gray                            | <a href="http://www.wago.com/793-4501/000-007">www.wago.com/793-4501/000-007</a> |
| <b>Item no.: 793-4501/000-012</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; orange                          | <a href="http://www.wago.com/793-4501/000-012">www.wago.com/793-4501/000-012</a> |
| <b>Item no.: 793-4501/000-017</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; light green                     | <a href="http://www.wago.com/793-4501/000-017">www.wago.com/793-4501/000-017</a> |
| <b>Group marker carrier</b>                                                                                                                  |                                                                                  |
| <b>Item no.: 209-142</b><br>Group marker carrier; gray                                                                                       | <a href="http://www.wago.com/209-142">www.wago.com/209-142</a>                   |
| <b>Item no.: 209-141</b><br>Group marker carrier; gray                                                                                       | <a href="http://www.wago.com/209-141">www.wago.com/209-141</a>                   |

Subject to changes. Please also observe the further product documentation!

**Item no.: 209-140**

Group marker carrier; gray

[www.wago.com/209-140](http://www.wago.com/209-140)**Item no.: 249-105**

Group marker carrier; gray

[www.wago.com/249-105](http://www.wago.com/249-105)**Mounting**

## Cover carrier

**Item no.: 709-167**

Cover carrier; Type 1; incl. fixing/retaining screws and knurled nut; suitable for 279 to 282 and 880 Series rail-mounted terminal blocks; suitable for 264 Series miniature rail-mounted terminal blocks; suitable for 270 Series sensor and actuator terminal blocks; gray

[www.wago.com/709-167](http://www.wago.com/709-167)

## Cover

**Item no.: 709-153**

Cover; Type 1; suitable for cover carrier, type 1; 1 m long; transparent

[www.wago.com/709-153](http://www.wago.com/709-153)

## Mounting accessories

**Item no.: 209-106**

Mounting carrier; for isolated mounting on DIN 35 rails; gray

[www.wago.com/209-106](http://www.wago.com/209-106)**Item no.: 249-116**

Screwless end stop; 6 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray

[www.wago.com/249-116](http://www.wago.com/249-116)**Push-in type wire jumper**

## Jumper

**Item no.: 249-123**Push-in type wire jumper; 0.75 mm<sup>2</sup>; insulated; 180 mm long; black[www.wago.com/249-123](http://www.wago.com/249-123)**Item no.: 249-126**Push-in type wire jumper; 0.75 mm<sup>2</sup>; insulated; 110 mm long; black[www.wago.com/249-126](http://www.wago.com/249-126)**Item no.: 249-127**Push-in type wire jumper; 0.75 mm<sup>2</sup>; insulated; 250 mm long; black[www.wago.com/249-127](http://www.wago.com/249-127)**Item no.: 249-125**

Push-in type wire jumper; insulated; 60 mm long; black

[www.wago.com/249-125](http://www.wago.com/249-125)**Testing and measuring**

## Testing accessories

**Item no.: 209-170**Test plug adapter; 8.3 mm wide; for 4 mm Ø test plugs; suitable for 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup> tbs; gray[www.wago.com/209-170](http://www.wago.com/209-170)**Item no.: 280-404**Test plug adapter; 5 mm wide; for test plug (2.3 mm Ø); suitable for 1.5 mm<sup>2</sup> - 4 mm<sup>2</sup> tbs; gray[www.wago.com/280-404](http://www.wago.com/280-404)**Insulation stop**

## Insulation stop

**Item no.: 279-470**Insulation stop; 0.08 - 0.2 mm<sup>2</sup> "s" (0.14 mm<sup>2</sup> "f-st"); 5 pieces/strip; white[www.wago.com/279-470](http://www.wago.com/279-470)**Item no.: 279-471**[www.wago.com/279-471](http://www.wago.com/279-471)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.





Insulation stop; 0.25 mm<sup>2</sup>; 5 pieces/strip; dark gray

#### Jumpers

| Jumper                                                                                            |                                                                |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Item no.: 279-402</b><br>Jumper; insulated; gray                                               | <a href="http://www.wago.com/279-402">www.wago.com/279-402</a> |
| <b>Item no.: 279-409</b><br>Jumper; insulated; gray                                               | <a href="http://www.wago.com/279-409">www.wago.com/279-409</a> |
| <b>Item no.: 279-422</b><br>Jumper; insulated; yellow-green                                       | <a href="http://www.wago.com/279-422">www.wago.com/279-422</a> |
| <b>Item no.: 279-492</b><br>Jumper; 2-way; insulated; gray                                        | <a href="http://www.wago.com/279-492">www.wago.com/279-492</a> |
| <b>Item no.: 279-490</b><br>Jumper; 10-way; insulated; gray                                       | <a href="http://www.wago.com/279-490">www.wago.com/279-490</a> |
| <b>Item no.: 279-482</b><br>Jumper; 2-way; insulated; gray                                        | <a href="http://www.wago.com/279-482">www.wago.com/279-482</a> |
| <b>Item no.: 279-483</b><br>Jumper; 3-way; insulated; gray                                        | <a href="http://www.wago.com/279-483">www.wago.com/279-483</a> |
| <b>Item no.: 284-414</b><br>Step-down jumper; from 284/282 to 281/280/279 series; insulated; gray | <a href="http://www.wago.com/284-414">www.wago.com/284-414</a> |

#### Ferrule

| Ferrule                                                                                                                        |                                                                |
|--------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Item no.: 216-101</b><br>Ferrule; Sleeve for 0.5 mm <sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored  | <a href="http://www.wago.com/216-101">www.wago.com/216-101</a> |
| <b>Item no.: 216-102</b><br>Ferrule; Sleeve for 0.75 mm <sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored | <a href="http://www.wago.com/216-102">www.wago.com/216-102</a> |
| <b>Item no.: 216-103</b><br>Ferrule; Sleeve for 1 mm <sup>2</sup> / AWG 18; uninsulated; electro-tin plated                    | <a href="http://www.wago.com/216-103">www.wago.com/216-103</a> |
| <b>Item no.: 216-203</b><br>Ferrule; Sleeve for 1 mm <sup>2</sup> / AWG 18; insulated; electro-tin plated; red                 | <a href="http://www.wago.com/216-203">www.wago.com/216-203</a> |
| <b>Item no.: 216-202</b><br>Ferrule; Sleeve for 0.75 mm <sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray             | <a href="http://www.wago.com/216-202">www.wago.com/216-202</a> |
| <b>Item no.: 216-201</b><br>Ferrule; Sleeve for 0.5 mm <sup>2</sup> / 20 AWG; insulated; electro-tin plated; white             | <a href="http://www.wago.com/216-201">www.wago.com/216-201</a> |
| <b>Item no.: 216-301</b><br>Ferrule; Sleeve for 0.25 mm <sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow           | <a href="http://www.wago.com/216-301">www.wago.com/216-301</a> |
| <b>Item no.: 216-302</b><br>Ferrule; Sleeve for 0.34 mm <sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise  | <a href="http://www.wago.com/216-302">www.wago.com/216-302</a> |

Subject to changes. Please also observe the further product documentation!



### Protective warning marker

Cover

Item no.: 279-415

Protective warning marker; 5-pole; with high-voltage symbol, black; yellow

[www.wago.com/279-415](http://www.wago.com/279-415)

### Downloads

#### Documentation

#### Additional Information

pdf  
2.3 MB  
Download

### CAD/CAE-Data

#### CAD data

2D/3D Models 279-604

URL  
Download

#### CAE data

EPLAN Data Portal 279-604

URL  
Download

ZUKEN Portal 279-604

URL  
Download

WSCAD Universe 279-604

URL  
Download

### Environmental Product Compliance

#### Compliance Search

Environmental Product Compliance 279-604

URL  
Download

4-conductor through terminal block; 1.5 mm<sup>2</sup>; suitable for Ex i applications; lateral marker slots; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 1,50 mm<sup>2</sup>; blue

### Installation Notes

#### Installation

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.




Snapping a terminal block onto the DIN-rail.



Quick assembly keys prevent reverse mounting.



Removing a terminal block from the assembly.



Steel DIN-rails are not suited for PEN (ground and N-conductor) applications per EN 60947-7-2 (VDE 0611, Part 3).

#### Conductor termination



#### CAGE CLAMP® connection

Inserting a conductor.



#### CAGE CLAMP® connection

Inserting a conductor.

With ferruled conductors, it is necessary to use a terminal block one size larger than the conductor's nominal cross-section.

Subject to changes. Please also observe the further product documentation!



Inserting insulation stops.



**CAGE CLAMP®** connection

Removing a solid conductor.

### Commoning



Commoning using an adjacent jumper.

Push jumper down until fully inserted!

### Testing



Testing with a test plug.

Picture shows a test plug adapter (209-170).


### Cover

Subject to changes. Please also observe the further product documentation!



Protective warning markers inserted into the operating slots

### Marking



Labeling via WMB Multi Marking System.

Subject to changes. Please also observe the further product documentation!