


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-4 @20°C	2.15 ohms max.
D.C. RESISTANCE	2-3 @20°C	0.050 ohms max.
D.C. RESISTANCE	6-10 @20°C	0.14 ohms max.
INDUCTANCE	1-4 66kHz, 100mVAC, Ls	1.55mH ±10%
LEAKAGE INDUCTANCE	1-4 tie(2+3, 6+10), 100kHz, 100mVAC, Ls	25.0uH typ., 50.0uH max.
DIELECTRIC RATING	4-10 tie(1+3), 3750VAC, 1 second	3000VAC, 1 minute
URNS RATIO	(4-1):(10-6)	7.142:1, ±1%
URNS RATIO	(4-1):(3-2)	7.692:1, ±1%
RESONANT FREQUENCY	-	500kHz min.



6E Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64	DRAWING TITLE	PART NO.	
6E	2/23	Method: Tray		Decimals: ±.005 [.13]	TRANSFORMER	750871032	
6D	3/21	PKG-0887		Footprint: ±.005 [.13]			
6C	1/15	www.we-online.com/midcom		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.			
6B	12/12	SEE REVISION SHEET FOR REVISION LEVEL					eiSos p/n: 750871032
							SPECIFICATION SHEET 1 OF 1