NOTES:		135104-RI-XX.	XX	
I. PACKAGE CABLE ASSEMBLY IN BAG. TAG IN BAG WITH "AMPHENOL CONNEX, I35104-RI-XX.XX AND DAT		DRAWING NO.		
		THIRD ANGLE PROJ.		RELEASE
2. FOR ASSEMBLY INSTRUCTIONS SEE END CONNECTOR PRINTS. 3. CABLE ASSEMBLY TO BE 100% TESTED FOR CONTINUITY, SHORTS AND OPEN.				
•	LENGTH XX,XX	(SEE TABLE)		
		2) 	
ORIENT R/A SMA AXIS SHOWN WITH RESPECT TO R/A SMA WITHIN ±10°	PART NUMBE 135104-RI-06 135104-RI-10 135104-RI-12 135104-RI-24 • ADDITIONAL LE BY CHANGING 2	.00 06.00 .00 10.00 .00 12.00		5
DESIGN REQUIREMENTS: FREQUENCY TO VSWR INS. LOSS dB MAX OTHER				009-881-380 A/ 132111 2 PART NUMBER QT
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL \pm .015 (0,381 mm)MATERIALMOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise, in any manner licensing, granting rights or permitting such holder or any other person to monufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.MATERIAL	DRAWN KARTH ENGIN KARTH APPRO CAD F Root	IK R EER IK R VED	DATE 03-Dec-10 DATE 03-Dec-10 DATE /135104-R1	SMA R/A DIRECT SO USING 0.085" CONI XX.XX" LENGTH

R	EVISIONS					
RIPTION		DATE	ECO	APPR		
SE TO MFG.		03-Dec-	10	KR		
				Ĩ		
		SCAL E	0.500	Ţ		
		{				
/R 2 2 I Ty ITEM	SMA R/A D	ONFORMABLE CAB DIRECT SOLDER PI ESCRIPTION	LUG	II SH		
SOLDER PLUG TO SOLDER PLUG, NFORMABLE CABLE, SCALE: 2.2:1 SHEET 1 OF 1 DWG SIZE DRAWING NO.						
B 135104-RI-XX,XX A						