

NUMBER C-179458

METRIC



名称 NAME	トレイケース 型番 TRAY P/N	数量 (ヶ) QTY'S	コネクタ型番 (バラ状) CONNECTOR P/N (L/P)	極数 Pos	トレイケース詰 コネクタ型番 IN TRAY P/N
		130	3-179394-0	30	3-179458-0
		170	2-179394-2	22	2-179458-2
		300	1-179394-0	10	1-179458-0
		400	0-179394-6	6	0-179458-6

単位: 概 DIMENSIONS IN MM. DO NOT SCALE PRINT

PRINT DIST

Copyright ©19 年 AMP (Japan) LTD. ALL RIGHTS RESERVED.		AMP 日本エー・エム・ピー株式会社 Tokyo, Japan	
一般公差 (GENERAL TOLERANCE) 10mm以下: ±0.2 10mm以上 30mm以下: ±0.25 30mm以上 100mm以下: ±0.3 角 度: ±3°		包合電線断面積 (WIRE RANGE) —//— mm ² (AWG -) 被覆外径 (INSULATION DIA.) —//— mmφ	
A 変更 FJ00-1591-94 7/25/94 K.A.S.K		材料 (MATERIAL) 仕上 (FINISH) —//— —//—	
O 作成 FJ00-0334-94 K.A.S.K 1/24/94		尺度 (SCALE) LOC 番号 (No.) —//— A J C-179458	
LTR 変更 (REVISION RECORD) DR CHK DATE		REV. SHEET A 1 OF 1	
DR. 1/24 '94 K. ASAKAWA DE. 1/24 '94 K. ASAKAWA		名称 (NAME) BLISTER TRAY PACKING.	
CHK. 1/24 '94 S. KUBOUCHI APP.		2.0 A-F CONN. TAB ASSEMBLY	