



**PROPRIETARY INFORMATION:**  
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 23374, BS	08/17/12	HM




**GENERAL SPECIFICATIONS:**

- RATING: 10A / 250V AC
- CABLE TYPE / SIZE: H05VV-F, 3 x 1.0 mm<sup>2</sup>
- TEMPERATURE RATING: 70° C
- CONDUCTOR COLORS: BROWN / BLUE/ GREEN-YELLOW
- CABLE JACKET COLOR: BLACK
- OVERALL LENGTH (L): 2500 ± 50 mm
- CABLE OUTER DIAMETER: 7.1 ± 0.2 mm
- END 'A' PLUG; CEE 7/7
- END 'B' IEC 320 / C13, RIGHT ANGLE
- APPROVALS PLUG: VDE, N, S, D, FI, KEMA, UTE, CEBC, OVE, IMQ
- APPROVALS CABLE: VDE, N, S, D, FI, KEMA, SEV, CEBC, OVE
- APPROVALS CONNECTOR: VDE, N, S, D, FI, KEMA, UTE, CEBC, OVE, IMQ, ASEV



**PACKING:**


HANKING



**NOTES:**

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
<b>TABULATION BLOCK</b>				
			<b>TOLERANCES:</b> DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005 MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013	 <b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
INIT.BY: BS	DATE: 08/17/12	FSCN No.: G, CC, YL	SIZE: A	REV. A
DRAWN: NF	DATE: 08/17/12	SCALE: NONE	PART NO: 23144272M5702-T(R)	SHEET 1/1

**Foot Note:**  
 Globtek Inc. will not be liable for the safety and performance of these power repair are subject to change without prior notice occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

**Limitation of Use:**  
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice