



FILTER	CAPACITANCE	M3	4-40 UNC	PART NO.
TYPE 1	180pF±20%	24-3811750X	24-3811630X	
TYPE 3	370pF±20%	24-3811790X	24-3811670X	
TYPE 4	830pF±20%	24-3811830X	24-3811710X	

NOTES:

1. RoHS COMPLIANT
2. METAL SHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATORS: PBT GF UL 94 V-0, BLACK
4. CONTACTS: COPPER ALLOY
 PLATING: § USE A FOR QUALITY CLASS 3
 § USE B FOR QUALITY CLASS 2
 § USE C FOR QUALITY CLASS 1
5. THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. ADAPTER SCREW: COPPER ALLOY; NICKEL PLATED
7. CAPACITANCE: SEE TABLE
8. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
9. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
10. CONNECTOR IS PART MARKED: [PART-NO.] CONEC [ABC]



THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

1997	date	name	tolerance	scale:	material:	title:
drawn	28.01.	Barcinski	2:1 (5:1)	SEE NOTES		HD FILTER ADAPTER
appd.	28.01.	Mickenbecker				62 polig
norm						
d-old						

dwg no:	CAD/ REL.13	DIN-A
	24K1Q0A	3
product no:	SEE TABLE	sh: 1/1

